

**ELITE DEVELOPMENTS
MAIN STREET TO KILLALY AND ELIZABETH STREET TO LORAIN STREET,
PORT COLBORNE**

**PROPOSED RESIDENTIAL PLAN OF SUBDIVISION
CITY OF PORT COLBORNE**

PROJECT No.: 21247

**FUNCTIONAL SERVICING & STORMWATER
MANAGEMENT REPORT**

Prepared For:

ELITE DEVELOPMENTS

Prepared By:

The Odan/Detech Group Inc.

Original: April 18, 2024

TABLE OF CONTENTS

1.0	BACKGROUND.....	1
2.0	SCOPE OF WORK.....	1
3.0	SANITARY SERVICING	2
	Existing Infrastructure and Background	2
	Existing Capacity at Seaway Treatment Plant	2
	Proposed Sanitary Servicing	3
4.0	WATER DISTRIBUTION	7
	Existing Infrastructure and Background	7
	Models.....	10
	Results	10
	Discussion of water distribution	21
5.0	STORMWATER MANAGEMENT CONSIDERATIONS	22
	INTRODUCTION.....	22
	GOAL OF THE STORM WATER MANAGEMENT DESIGN	22
	TARGET FLOW	28
	POST-DEVELOPMENT CONDITIONS	31
	METHODOLOGY	32
	HYDRAULIC ANALYSIS:	32
	DISCUSSION OF XP2D MODEL:	43
	MODELLING RESULTS:.....	44
	EROSION REVIEW:.....	69
	REVIEW OF INGRESS/EGRESS AND RISK ASSESSMENT	74
	WATER QUALITY	75
	WATER BALANCE/GROUNDWATER	79
	SPECIAL SERVICING REQUIREMENTS DUE TO ROCK AND GROUNDWATER	82
	WETLAND ASSESSMENT	82
	DISCUSSION/COMMENTARY AND OBSERVATIONS	82
6.0	GRADING CONSIDERATION	83
7.0	RECOMMENDATIONS	84
8.0	CONCLUSIONS	84
9.0	REFERENCES.....	85

LIST OF FIGURES

Figure 1 – Location of Elite Development (Planned Development).....	1
Figure 2 – Location of Existing Pump Station Relative to Subject Site	2
Figure 3 – Region of Niagara Water Model (existing).....	11
Figure 4 – Region of Niagara Water Model (Elite added)	12
Figure 5 – Pre-Development with 2041 Peak Hour Demand	13
Figure 6 – Post-Development with 2041 Peak Hour Demand.....	14
Figure 7 – Pre-Development with 2041 Peak Hour Demand + Fire	15
Figure 8 – Post-Development with 2041 Peak Hour Demand + Fire	16
Figure 9 – Post-Development Available Fire Flow with 2041 PH Demand (detail of Elite Site) ..	17
Figure 10 – Pre-Development with 2041 Minimum Hour Demand.....	18
Figure 11 – Post-Development with 2041 Minimum Hour Demand	19
Figure 12 – Pre and Post Pressure Distribution Plot.....	20
Figure 13 – Elite Development location relative to existing drainage sheds.....	23
Figure 14 – Wignell Drain Study Area Hydrological Subcatchments Existing Conditions.....	24
Figure 15 – PCSWMM model of Wignell Drain Study Area Existing Conditions.....	25
Figure 16 – PCSWMM model of Wignell Drain showing node (junction) numbering	26
Figure 17 – Adjusted Provincial 2018 DEM for the study area.....	31
Figure 18 – XPSWMM Global Existing model	38
Figure 19 – XPSWMM existing model showing Tributary areas and node links.....	39
Figure 20 – XPSWMM Global Elite Site Developed model.....	40
Figure 21 – XPSWMM Elite Site Developed model showing Tributary areas and node links.....	41
Figure 22 – Close up of urbanized XPSWMM Elite Site Developed model.....	42
Figure 23 - XPSWMM depth MAP (100year) - site undeveloped existing flows	45
Figure 24 - XPSWMM depth MAP (50year) - site undeveloped existing flows	46
Figure 25 - XPSWMM depth MAP (25year) - site undeveloped existing flows	47
Figure 26 - XPSWMM depth MAP (10 year) - site undeveloped existing flows	48
Figure 27 - XPSWMM depth MAP (5 year) - site undeveloped existing flows	49
Figure 28 - XPSWMM depth MAP (2 year) - site undeveloped existing flows	50
Figure 29 - XPSWMM hazard MAP (100year) - site undeveloped existing flows	51
Figure 30 - XPSWMM bed shear MAP (100 year) - site undeveloped existing flows	52
Figure 31 - XPSWMM bed shear MAP (2 year) - site undeveloped existing flows	53
Figure 32 - XPSWMM depth MAP (100year) - Elite Site developed	54
Figure 33 - XPSWMM depth MAP (50year) - Elite Site developed	55
Figure 34 - XPSWMM depth MAP (25year) - Elite Site developed	56
Figure 35 - XPSWMM depth MAP (10 year) - Elite Site developed	57
Figure 36 - XPSWMM depth MAP (5 year) - Elite Site developed	58
Figure 37 - XPSWMM depth MAP (2 year) - Elite Site developed	59
Figure 38 - XPSWMM hazard MAP (100 year) - Elite Site developed	60
Figure 39 - XPSWMM bed shear MAP (100 year) - Elite Site developed.....	61
Figure 40 - XPSWMM bed shear MAP (2 year) - Elite Site developed	62
Figure 41 - XPSWMM depth MAP- Existing – 100 yr Lake – 10 yr storm	71
Figure 42 - XPSWMM depth MAP- Elite developed – 100-yr Lake – 10-yr storm	72
Figure 43 – 3D view of post-developed graded Site	83

LIST OF TABLES

Table 1. Summary of Scenarios run and assumptions made.....	8
Table 2. Elite Developments demand calculations	8
Table 3. Elite Developments demand calculations	10
Table 4. Target flow locations for the Wignell Drain	28
Table 5. Pre-Development Existing Flow Targets.....	28
Table 6. Post Development hydrology parameters.....	37
Table 7. Required Storage Volumes Elite Site Developed.....	44
Table 8. Comparison of Pre-Development and Developed Site Pond flows.	44
Table 9. Summary of hydraulic effects existing and Elite Site Developed.....	64
Table 10. XPSWMM comparison of Outflow – existing (target) and redeveloped	70
Table 11. Summary of Lake effects - hydraulic effects existing and Elite Site Developed.....	73

LIST OF APPENDICES

APPENDIX A – General

Aerial Photo of Existing Site
Draft Plan of Proposed Development (reduced)

APPENDIX B – Sanitary Servicing

Figure S-1 - Proposed Global Sanitary Servicing (Schematic)
Figure S-2 - Conceptual Sanitary Servicing (Option 1)
Figure S-3 - Conceptual Sanitary Servicing (Option 2)
Figure S-4 - Sanitary Tributary Plan

APPENDIX C – Water Distribution

INFOWATER Pro (715023 - Port Colborne Water Model - MSP.aprx) existing and updated
Provided upon request.

APPENDIX D – Stormwater Management

Figure S-5 - Pre-Development Catchment Areas
Figure S-6 - Post-Development Catchment Areas (Local)
Figure S-7 - Conceptual Storm Servicing Plan
Figure S-8 - Conceptual Grading Plan
Figure S-9 to S-16 - Conceptual Pond Sections (Ponds A-F)

1.0 BACKGROUND

The property under study is a 142.27ha (351.56 acres) proposed for residential development site in the City of Port Colborne. The site is bounded by Elizabeth Street to the west, Main Street to the north, Lorraine Street to the east and Killaly Street East to the south. The site is east of the Welland Canal. The lands are predominately vacant and are currently being utilized as Agricultural Lands. Refer to Figure 1 for the extends of the subject property.

It is proposed to develop the lands for residential and commercial use with related streets and parking.

The purpose of this document is to provide a Functional Servicing and Storm Water Management strategy assessing the serviceability and identifying potential constraints and encumbrances that would limit the sites potential for the intended development based on available information.

For detailed topography of the existing site conditions refer to the topographic survey and for a detailed Conceptual site plan prepared by Weston and Associates refer to Appendix A.

2.0 SCOPE OF WORK

THE ODAN/DETECH GROUP INC. was retained by **ELITE DEVELOPMENTS** to review the Site, collect data, evaluate the Site for the proposed use and present the findings in a Functional Servicing and Storm Water Management Report in support of an OPA/Rezoning Application and Draft Plan of Subdivision Application. The scope of work in brief involves the following:

- a) Collecting existing servicing drawings from the CITY/REGION in order to establish availability and feasibility of Site servicing;
- b) Meetings/conversations with CITY/REGION Engineers, Niagara Peninsula Conservation Authority and Design Team.
- c) Evaluation of the data and presentation of the findings in a FSR and Storm Water Management Report in support of the OPA/Rezoning and Draft Plan of Subdivision Application.

Figure 1 – Location of Elite Development (Planned Development)




Figure 1 above shows the location of the Elite properties to be developed.

Red lines above represent Elite's proposed development.

3.0 SANITARY SERVICING

Existing Infrastructure and Background

The proposed development extends from east of Elizabeth Street to Lorraine Street and from south of Main Street to Killaly Street. There are no sanitary sewers within subject lands and the existing sewers do not have sufficient capacity to convey the proposed waste water flows.

The existing Fretz Sanitary Pump Station (SPS), located south of the site on Johnston St between James St and Mercury Ave, was considered to be upgraded for portions of the site located near the SPS however due to existing high inflow and infiltration (I&I) contributing to the Fretz SPS, retrofitting the station would be difficult to undertake (see Figure 2 below for location of Fretz SPS relative to the subject site). Our discussions with City of Port Colborne and Niagara Region staff revealed that the Fretz SPS is relatively old and the existing forcemain outlet is near the end of its service life, which doesn't warrant an upgrade. In addition, the forcemain outlets to a gravity sewer that doesn't have the capacity to add additional flow from the subject site.




Figure 2 – Location of Existing Pump Station Relative to Subject Site

Existing Capacity at Seaway Treatment Plant

The existing Seaway Wastewater Treatment Plant (WWTP) located at 30 Prosperity Ave services the entire City of Port Colborne and is located north-west of the site on the west side of the Welland Canal. According to the Niagara Region Master Servicing Plan Update dated June 2023, the existing WWTP has the capacity to support growth up to 2051 which includes population from the subject development.

Proposed Sanitary Servicing

Sanitary Pump Station

Due to the absence of existing sanitary servicing to the site, Odan/Detech met with the City of Port Colborne and Niagara Region to discuss feasible sanitary servicing strategies for the site. Niagara Region expressed that the preferred strategy is to propose a new pumping station within the subject lands with a forcemain routed to the Seaway WWTP. The forcemain route is proposed to run north along Elizabeth Street to Second Concession Rd, turn west toward the Welland Canal and cross to Barrick Rd through a new tunnel beneath the canal being proposed, where it will connect south from Barrick Rd to the existing Seaway WWTP. The service tunnel beneath the canal is currently proposed to be constructed in 2026 according to the City and Region. Please refer to Figure S-1 in Appendix B for the proposed layout of the forcemain connection to the Seaway WWTP.

Several factors, namely site phasing, bedrock depth, sewer depth and crossing the existing floodplain within the site, led to determining suitable locations for a new sanitary pump station within the site. Two options were considered shown on Figure S-2 and S-3 in Appendix B.

The first option shown in Figure S-2 proposes the SPS at the west end of the site fronting Elizabeth Street, south of the northwest woodlot, which is likely within the limits of the first phase of development. Although this location allows for a reduced forcemain length to the Seaway WWTP, it requires longer gravity sewers to reach the extremities of the areas to be serviced, thereby requiring deeper sewers and additional bedrock removal.

A second option has been considered which locates the SPS in a central location, north of the floodplain fronting the Snider Rd road allowance running north-south through the centre of the site (see Figure S-3). This location allows for comparable sewer run lengths in multiple directions servicing the required sanitary service boundaries and shallower sewers. This location of the site shows to have a deeper bedrock depth which reduces bedrock removal for both sewer excavation and the SPS wet well compared to the first option.

Comparing both above SPS locations, the second option is the preferred location from a construction cost and phasing standpoint. The reduced bedrock excavation will significantly lower the costs to service the site and being centrally located will allow for greater flexibility to delineate phasing within the site.

In discussion with the City and Region it was requested that additional land area outside the subject site be included in the drainage area for the proposed SPS. These areas are located between the Snider Rd road allowance and Lorraine St, south of Hwy 3 and also south of Killaly Street East. Please refer to Figure S-4 in Appendix B showing the additional drainage areas to be included in the SPS service area. The total service area for the new SPS is 124 hectares.

The SPS details will be determined at a later date once the site-specific details regarding population horizons and SPS locations are finalized. Based on the Niagara Region Water-Wastewater Project Design Manual and anticipated flows (see following discussion), the SPS will be a single wet well with a bypass inlet maintenance hole. It will be equipped with one or more pumps with a combined capacity equal to the design flow. The lot size needed for the SPS is expected to be a minimum of 25m x 25m.

Total Sanitary Flow Generation

To determine the total sanitary flow that the new SPS will service, the population of the subject site and external drainage boundaries were determined.

For calculating the population of the subject site, the criteria below was used for determining the population of different unit types.

- 2.7 persons/unit for town homes
- 3.4 persons/unit for single detached

Using the above criteria, the following population is derived for the subject site.

Unit Type	Number of Units	People per Unit	Total Population
Single Detached	1027	3.4	3,492
Townhomes	1215	2.7	3,281
Total Residential Population			6,773

For sanitary drainage areas outside the subject development, the number of estimated units is unknown however it is assumed that the housing density will be similar to the subject site. To estimate an appropriate people per hectare (pph) value for external areas, the subject site's pph value was determined using the total net developable area of the site (excluding SWM ponds and regulated areas), less the assigned commercial area yielding a total area of 97.18ha. The pph value for the subject site based on the above residential total is 70pph. This population density will be used to estimate the population of external areas contributing to the new SPS within the development.

The criteria used to calculate the total sanitary flow is based on the following Niagara Region parameters.

- Residential flow rate of 255 L/person/day
- 5.0 L/day/m² of commercial floor area
- Peaking factor using Harmon formula (between 2 and 4)
- Infiltration – 0.286 L/s/ha (for new developments)

Based on the above parameters, the total peak sanitary flow contributing to the new SPS was calculated to be **111.55 l/s**. Refer to the following calculation breakdown for further details.

SANITARY FLOW CALCULATIONS

This spread sheet calculates the sanitary discharge from various land use as per the Niagara Region Guideline

Total Site Area (ha)	99.68
Total External Area (ha)	24.37

LAND USE	NUMBER OF UNITS	AREA (ha)	GROSS FLOOR AREA, m ²	TOTAL POPULATION	TOTAL DAILY FLOW (LITERS)	AVERAGE DAILY FLOW l/sec	PEAKING FACTOR, M	TOTAL FLOW FROM LAND USE, l/sec
RESIDENTIAL Single Detached 3.40 person/unit	1,027			3,492	890,409	10.31		
RESIDENTIAL Townhomes 2.70 person/unit	1,215			3,281	836,528	9.68		
External Future Residential 70pph		24.37		1,706	435,005	5.03		
Total Residential				8,478	2,161,941	25.02	3.03	75.71
COMMERCIAL 5 L/DAY/m ²			6250		31250	0.36		
Total Commercial					31250	0.36	1.00	0.36
Infiltration		124.05						35.48
Total Flow (l/s)								111.55

$$Q = (M \cdot q \cdot P / 86400) + A \cdot I \quad (\text{L/sec})$$

Q1= total flow from Residential Land Use (L/sec)
Q2= total flow from Commercial Land Use (L/sec)
Qinfil = total flow from infiltration (L/sec)
Qtot = total flow (Q1 + Q2 + Qinfil)

where : P is population
q(res) = 255 L/person/day for residential
A = gross site area
i = 0.286 L/sec/ha (infiltration rate)
Peaking Factor $M = 1 + [14 / (4 + (P/1000,1/2))]$
(Between 2 and 4)
q(comm)=5.0 L/d /m2 total floor area for Commercial Retail

Forcemain Sizing

The proposed forcemain outletting to the Seaway WWTP shall be designed in accordance with MECF Guidelines and Niagara Region standards which requires the flow velocity to range from 1.0m/s to 2.0 m/s. Preliminary sizing of the forcemain suggests that a 300mm forcemain (twinning for redundancy) is considered sufficient to service the SPS however this size may change based on the final detailed design. Maintaining the minimum velocity will ensure that sediment does not accumulate within the forcemain therefore the sanitary flow rates for each phase of development and corresponding pump size will be evaluated during the detailed design phase.

The forcemain design will be undertaken by the Region of Niagara at a later date once the site-specific details regarding population horizons and SPS locations are finalized.

Sanitary Sewer Distribution

Schematic sanitary sewer distribution concepts have been prepared for the subject development for two options discussed above which slightly vary depending on the proposed SPS location. Please refer to Figure S-2 and S-3 in Appendix B for details of the conceptual layouts.

The main difference between both options is the depth of the sewer in the north-west quadrant of the site which is due to the placement of the SPS as mentioned previously. An additional 3m of sewer depth is required to run the sewer to the SPS located along Elizabeth St as opposed to centrally locating it adjacent to the Snider Rd road allowance north of the floodplain.

It is anticipated that phasing of the site will progress from west to east therefore should the SPS be centrally located it will need to be constructed in isolation from the first phase of development. Temporary access to service the SPS in Option 2 would need to be considered.

To service the areas of the subject site east of the floodplain, a sanitary sewer crossing beneath the floodplain along the Snider Rd road allowance will be required. The method of crossing the flood plain will be determined at the detailed design stage. This crossing is relatively deep (approximately 10m) and does not vary between both schematic sewer options. The need for the significant sewer depth is to be able to reach the sewer to the south-east extremities of the site, including allocated external development areas, while meeting City standard sewer depths at the far reaches of the sewer.

Due to the size of the development and substantial rock removal that will be required, it is expected that main sewer runs to the furthest points of the development leading from the SPS will be relatively low percentage slopes to minimize the depth of the SPS and rock removal along the sewers. However please note that in the final design stage of the sewers, MECP and City standards will be followed to ensure adequate pipe sizes and slopes are proposed to provide self-cleansing velocities within the sewer.

4.0 WATER DISTRIBUTION

Existing Infrastructure and Background

The proposed development is located in PD1 (only pressure district) of the City of Port Colborne water distribution network and will be serviced by connecting to and extending pipes from the existing network through the proposed development. To support the proposed developments, this report presents and discusses the results of a hydraulic investigation and hydraulic modelling analysis of the existing City water model. The analysis assesses whether the existing water infrastructure has adequate capacity to support the proposed development, and what system expansions and upgrades (if necessary) are required.

The Region of Niagara created a INFOWATER Pro (715023 - Port Colborne Water Model - MSP.aprx) distribution model which included the entire City. Odan/Detech procured a copy of the Model from the Region of Niagara.

We are assuming the following about the City water model:

- City water system model data, including mains (pipes), junctions, valves, chambers, hydrants and pressure district boundaries represents the existing conditions in-situ.
- Model is calibrated and represents the pressures and flows as they are now with existing demands.
- The Model can be relied upon for predicting future conditions.
- Development details for the Elite Development (e.g., unit counts, commercial area breakdown, development statistics, etc.) as set out in the Concept Plans prepared by Weston Consultants.

In addition, we are relying on the following:

- **DESIGN GUIDELINES FOR DRINKING WATER SYSTEMS**, by the Ministry of the Environment of Ontario (now The Ministry of the Environment, Conservation, and Parks; MECP), dated 2008.
- **NIAGARA REGION WATER-WASTEWATER PROJECT DESIGN MANUAL, Revision 3**, July 2023.
- **THE CITY OF WELLAND MUNICIPAL STANDARDS DESIGN CRITERIA**, February 2013.

The analysis presented in this report will include hydraulic simulations of the

- Minimum Hour (MHD),
- Maximum Day (MDD),
- Peak Hour plus Fire (MDD + FF) and the (Niagara Region Standard)
- Peak Hour (PHD) demands.

The above will be performed for the existing conditions and the Elite Development added. The two will be compared. The following Table 1 is a summary of the scenarios run and the hydraulic assumptions made.

Table 1. Summary of Scenarios run and assumptions made

Development Condition	Demand	ADD Multiplier	Barrick Road ET Water Level	Number of Pumps in Service	Fire Flow
Pre-Development	2041 Peak Hour	2.8	7.8 m (60%)	2	-
Post-Development	2041 Peak Hour	2.8	7.8 m (60%)	2	-
Pre-Development	2041 Peak Hour + Fire	2.8	7.8 m (60%)	2	Fire demand of 318 L/s at node 33001115 as per Region's hydraulic model
Post-Development	2041 Peak Hour + Fire	2.8	7.8 m (60%)	2	Fire demand of 318 L/s at node 33001115 as per Region's hydraulic model
Post-Development	2041 Peak Hour	2.8	7.8 m (60%)	2	Available fire flow assessed for subject development subject to maintaining 140 kPa
Pre-Development	2041 Minimum Hour	0.16	12.4 m (96%)	1	-
Post-Development	2041 Minimum Hour	0.16	12.4 m (96%)	1	-

It should be noted that the Elite Development will take the City to the 2041 time line, which will add approximately 6800 persons. The following Table 2 are the calculated water demands for the subject site.

Table 2. Elite Developments Demand Calculations

TYPE	DESCRIPTION OF DEVELOPMENT	NUMBER OF UNITS	ICI (m2)	POPULATION	Average Day (RESIDENTIAL + ICI) (L/sec)	Peak Day (L/sec)	Peak Hour (L/sec)	Fire flow required (L/sec)	Total Flow required (Fire + max day) (L/sec)
RESIDENTIAL	SINGLE FAMILY	999	0	3397	12.58	22.39	35.22	75	97.4
RESIDENTIAL	TOWNHOMES	1,262	0	3407	12.62	22.46	35.34	120	142.5
					25.20				
COMMERCIAL	COM-1		1562.5	0	0.14	0.26	0.41	200	200.3
COMMERCIAL	COM-2		1562.5	0	0.14	0.26	0.41	200	200.3
COMMERCIAL	COM-3		1562.5	0	0.14	0.26	0.41	200	200.3
COMMERCIAL	COM-4		1562.5	0	0.14	0.26	0.41	200	200.3
					0.58				
TOTALS		2261	6250	6804	25.78	45.89	72.18	-	-
PEAK DAY FACTOR		1.78							
PEAK HOUR FACTOR		2.8							
SINGLE FAMILY		3.4 PPU							
TOWNHOME UNITS		2.7 PPU							
ICI DEMAND IS		8 L/Day/m2							
AVERAGE DAY		320 L/CAP/DAY							

The above includes the Elite property. We do not have any knowledge of density and style of development for the other infill properties not owned by Elite. The infill properties not owned by Elite will be included. The following standards will be used to make the analysis conservative thus including the infill properties in the analysis. The standards used above were from the City of Welland. Note the actual peak day and Peak hour multipliers used in the model were 2.8 for both. This is conservative. The City of Welland uses 320 L/cap/day. The Region of Niagara uses 255 L/cap/day.

The Welland demand is $(320 - 255 \div 255) = 25\%$ more demand. Coupled with the Peak Day being 2.8 which makes the analysis very conservative.

Refer to the Concept Site Plan by Weston Consulting in Appendix A for details of the Elite development and site statistics.

Models

The Region of Niagara created a INFOWATER Pro (715023 - Port Colborne Water Model - MSP.aprx) distribution model which included the entire City. As mentioned above this model will be used as a base. The addition of the Elite Development will be added to the base model. The scenarios as mentioned in Table 1 above will be run and results obtained and compared.

For detailed model input/output refer to the digital INFOWATER Pro and info in appendix C for the following:

- Model Output – Nodes
- Model Output – Pipes
- Model Output – Fire Flows
- Pressure Distribution – Data

Refer to Figure 3 for the Region of Niagara Water Model (existing) and to Figure 4 for Region of Niagara Water Model (Elite added).

Results

In addition to the above detailed output the following Results will be shown:

- Figure 5 Pre-Development with 2041 Peak Hour Demand
- Figure 6 Post-Development with 2041 Peak Hour Demand
- Figure 7 Pre-Development with 2041 Peak Hour Demand + Fire
- Figure 8 Post-Development with 2041 Peak Hour Demand + Fire
- Figure 9 Post-Development Available Fire Flow with 2041 PH Demand (detail of Elite Site)
- Figure 10 Pre-Development with 2041 Minimum Hour Demand
- Figure 11 Post-Development with 2041 Minimum Hour Demand

Note, all but Figure 9 are nodal pressure and pipe velocity plots.

Figure 9 shows the pipe sizes within the Elite development. Note, only the major distribution pipes were modelled (200mm, 250mm and 300mm). The numbers in the box near the nodes represent the available fire flows in L/sec.

Figure 12 represents in graphical format the predeveloped and post developed sites.

Table 3 below summarizes the range of pressure operations under the various demands.

Table 3. Elite Developments demand calculations

		Pre-Development 2041 PHD	Post-Development 2041 PHD	Pre-Development 2041 PHD+Fire	Post-Development 2041 PHD+Fire	Pre-Development 2041 MHD	Post-Development 2041 MHD
System Pressure (Entire System)							
	Max (kPa)	427	421	396	395	477	477
	Min (kPa)	158	151	128	116	333	332
System Pressure (Proposed Development)							
	Max (kPa)	-	379	-	327	-	440
	Min (kPa)	-	330	-	278	-	391

Figure 3 – Region of Niagara Water Model (existing)




Figure 4 – Region of Niagara Water Model (Elite added)



Figure 5 – Pre-Development with 2041 Peak Hour Demand



Figure 6 – Post-Development with 2041 Peak Hour Demand




Figure 7 – Pre-Development with 2041 Peak Hour Demand + Fire




Figure 8 – Post-Development with 2041 Peak Hour Demand + Fire




Figure 9 – Post-Development Available Fire Flow with 2041 PH Demand (detail of Elite Site)




Figure 10 – Pre-Development with 2041 Minimum Hour Demand




Figure 11 – Post-Development with 2041 Minimum Hour Demand





Figure 12 – Pre and Post Pressure Distribution Plot



The above plot is an encompassing result plot showing and comparing many things. For example, under full Elite buildout, and MHD (minimum hour demand) 100 % of the area has pressure less than 475 kPa. In addition, 0% of the area has a pressure less than 340 kPa under MHD. Note, in the beginning of the Elite development all the pre/post curves will be close to each other. As demand (development) increases the higher demands will show a more pronounced deviation in post/pre as shown above. In essence the top and bottom of the graph is the operating range of the system for that demand. Note, it is the long dead-end pipe at the north end of the system that shows poor pressure at the dead end. It is the same in the existing condition. It shows up in the above graph in the PHD and Fire flow demand (red and blue graphs).

Discussion of water distribution

- While distribution system pressures are predicted to decrease at full build-out of the study area, these are still within the City's acceptable pressure range.
- City Criterion normal Pressure Range 275 kPa (40 psi) to 690 kPa (100 psi) has been met.
- City Criterion Maximum Velocity 1.5 m/s has been met.
- Anticipate fire flows for the Elite Site has been met.
- Pressures through out the system is greater than 140 kPa (20 psi) during fire flows has been met.
- Exact fire demand can not be determined at this early stage. The values given in Table 2 should be sufficient.
- The system analysis assumes the supply of water to meet the demands will be available. The system supply side was not analysed.
- The Elite Development pipe routing is well looped. Note, only the major distribution pipes were modelled (200mm, 250mm and 300mm). The lesser pipes will be looped and routed in accordance with City standards.
- It is recommended that in the phasing of the Elite Development, that all pipes are looped, with only continuation stubs (+/- 1 m) left or a hydrant placed at the dead end.
- Note, it is the long dead end pipe at the north end of the system that shows poor pressure at the dead end. It is our understanding that the Region will rectify this in the future.

5.0 STORMWATER MANAGEMENT CONSIDERATIONS

INTRODUCTION

The proposed Elite Development is located within the Wignell Creek Sub watershed. Refer to Figure 13 for location of Elite proposed development.

Prior to embarking on the Storm Water Management (SWM) for Elite we reviewed the following reference reports:

1. **“Wignell Watershed Hydrology and Hydraulics Report”**, EWA Engineers Inc., August 31, 2021.
2. **“NIAGARA PENINSULA CONSERVATION AUTHORITY FLOOD PLAIN MAPPING WIGNELL DRAIN CITY OF PORT COLBORNE”**, NIAGARA PENINSULA CONSERVATION AUTHORITY, August 2011.

Report 1 above is The Wignell Drain Engineer's Report is prepared as follows:

- a. Baseline Drainage Report.
- b. Wignell Watershed Report.

Report 2 above was undertaken by (NPCA) to generate the regulatory 100-year flood plain mapping for the Wignell Drain Watershed in the City of Port Colborne. The generated flood plain extents will be used by the Niagara Peninsula Conservation Authority to regulate development within the 100-year flood plain, as mandated by the Conservation Authorities Act.

The subject report will be a hybrid of both reports, showing the drain capacities along with the flood HGL by incorporating the Culverts and their effects on the drains.

GOAL OF THE STORM WATER MANAGEMENT DESIGN

Stormwater management for the proposed development will set out the following goals:

1. Protect and manage quantity and quality of surface water and groundwater resources;
2. Mitigate or minimize the risk of flooding and erosion in the Sub watershed;
3. Preserve natural hydrological and hydrogeological systems;
4. Identify the aquatic, wetland and terrestrial resources that should be protected or enhanced;
5. Produce an implementation plan for Development of the Sub watershed Study area;
6. Provide recommendations for the responsible storm water management Plan on a sub watershed level, if applicable;
7. Develop an adaptive management guide for future activities in the sub watershed

Figure 13 – Elite Development location relative to existing drainage sheds





Figure 13 above shows that the Elite Development will drain to two distinct drainage systems:

1. Welland Canal south watershed.
2. Wignell Drain watershed.

Figure 14 below is a schematic of the PCSWM model used by EWA Engineers to evaluate the Wignell Drain. The schematic shows the drains in yellow and the dashed red lines are the hydrologic connectivity from the subcatchments to the hydrologic nodes, shown in green.


The following Figure 15 and 16 are the EWA color coded model showing the branches of the Wignell Drain with key crossing numbers and the Wignell Drain showing node (junction) numbering respectively.

Figure 14 – Wignell Drain Study Area Hydrological Subcatchments Existing Conditions



Total area = 1089.58 ha

Figure 14 – PCSWMM model of Wignell Drain Study Area Existing Conditions



The above Figure is from the EWA PCSWMM model for the Wignell watershed report.

PROJECT No. 21247
File No. 21247-ELITE-Port Colborne-FSR (April 2024).docx

EXISTING SUBCATCHMENT AREAS.

The Wignell drain total drainage area is 1089.58 ha. (from EWA PCSWMM model)

The Elite site as mentioned above has two drainage sheds as follows:

Total area to Welland Canal south watershed	52.28 ha
Total Wignell Drain watershed	1089.58 ha (same as above)

NOTES ON EWA REPORT and MODEL:

1. We have adapted the same hydrology as EWA (refer to Table 1 from the EWA report).
2. We will have to create a new subcatchment for our predevelopment and post development model for the Elite site area draining to the Welland Canal south watershed. The following will be used – existing - % impervious 1.0%, slope 0.1 %, width 480 m, CN =83, Area by DEM which is 52.28 ha.
3. PCSWMM model shows an area for sub-catchments PC7 of 54.01 ha, table 1 shows 46.29 ha.
4. PCSWMM model shows flow from the quarry areas plus the pump rates. The report table 2 shows the pump rate flow only. On page 21 of the report EWA states in the last paragraph on that page, the groundwater pump rate at the quarries were considered as the flow generated from the respective catchments and discharged into Wignell Drain.
5. EWA set Quarry contributing areas with a static outflow to model pumping set at two rates:
West Quarry = 0.057 m³/s, and
East Quarry = 0.118 m³/s.
We have adapted the same flow rates in the XPSWMM model.

TARGET FLOW

The above PCSWMM model was used to establish predevelopment hydrology target values to compare to the post developed conditions with the Elite development added. The following Table 4 summarizes the location where existing target flows will be compared to post developed conditions.

Table 4 Target flow locations for the Wignell Drain

No.	Location description or crossing	Notes
S-1	Hwy # 3 culvert crossing west branch	Should be similar to PCSWMM
S-2	Hwy # 3 culvert crossing east branch	Should be similar to PCSWMM
S-3	Killaly culvert crossing west of Snider Road	Should be similar to PCSWMM
S-4	Killaly culvert crossing east of Lorraine Road	
S-5	Snider road culvert crossing just north of Friendship Trail (former CNR)	
S-6	Friendship trail culvert crossing adjacent to Snider Road west side	
S-7	Outlet to Lake	

Table 5 below summarizes the allowable (target flows) for the existing outlets per storm event.

The comparison will be made with XPSWMM (2D) existing conditions and XPSWMM (2D) with Elite development added. It is the only reliable way to compare as the original PCSWMM model is not 2D and does not include the culverts in real time. The NPCA HEC-RAS model maintains continuity of flow and thus has no attenuation at culverts. We will include the flows of PCSWMM at the above locations for comparison only.

Table 5. Pre-Development Existing Flow Targets								
Storm Event	Storm Type	Target Peak Flow Rate (m ³ /s)						
		S-1	S-2	S-3	S-4	S-5	S-6	S7
		Existing	Existing	Existing	Existing	Existing	Existing	Existing
2 Year	24Hr SCS	0.439	0.730	1.070	0.685	1.025	1.026	0.479
5 Year	24Hr SCS	0.794	1.215	1.787	1.554	1.946	1.954	1.046
10 Year	24Hr SCS	1.054	1.591	2.357	2.326	2.521	2.531	1.484
25 Year	24Hr SCS	1.401	2.160	3.157	3.422	2.663	3.335	1.781
50 Year	24Hr SCS	1.646	2.651	3.873	4.239	2.694	3.848	1.966
100 Year	24Hr SCS	1.903	3.157	4.626	4.994	2.698	4.335	2.179
100 Year	12Hr AES	0.606	1.976	4.043	4.628	2.701	4.020	1.774

A development such as Elite requires a team approach with many disciplines. Planners, Environmental Consultants, Hydrogeologist/Soil Consultants and Civil Engineering Consultants. The development fabric was determined based on the Survey/Topographical Plan, Provincial Lidar derived DEM and the natural heritage features as determined by Palmer. Weston is the Planner, Palmer is the Environmental Consultants, EXP is the Hydrogeologist/Soil Consultant and Odan/Detech Group Inc. are the Civil Consultants.

The development fabric (Draft Plan of Sub-Division) was assembled by Weston through input by the Developer, Palmer, EXP and Odan/Detech group inc. Refer to Appendix A for the reduced version of the Draft Plan of Subdivision by Weston. It is recommended to utilize 6 (six) storm water management (SWM) ponds for the development of the Elite Port Colborne site as shown on drawing S-6 in Appendix D and on the Site Conceptual Plan in Appendix A. The ponds outlet to the Wignell Drain at various locations. The preferred method to determine an allowable (target flow) is to use the predevelopment unit runoff rates. The following is the procedure:

1. Pick a point in the drainage system where there is a known flow from PCSWMM model. The Elite site as mentioned above has two drainage sheds as follows:

Welland Canal south watershed - Point A ditch at Elizabeth Street (see Figure 13)

Wignell Drain watershed - Point B culvert crossing Killaly Street, west of Snider Road.

2. For the Welland Canal south watershed - Point A, the calculated flows are based on hydrology shown on page 23 above.
3. For the Wignell Drain – Point B, the following summarizes the target flow for 100-year flow. The procedure applies for all other flows.

Notes: The quarry areas were removed because they do not contribute runoff flow.

From PCSWMM model												unit rate m3/s/ha
Name	Area (ha)						Point B area (ha)		Point B flow (m3/sec)			
W10	8.32						274.24		6.86			0.025
W6	28.7457											
W2	26.526											
PC3-QW1	41.95											
PC4-QE1	18.79											
W1	16.7049											
PC7	19.3425											
W4	1.98											
M3	3.65											
W7	36.5969											
W3	66.06											
PC8	63.43											
PC2	7.7											
W14	20.8394											
M1	54.0114											
W13	39.1345											
M2	8.8715											
W11	5.4412											
W9	58.2949											
W5	100.6											
PC6	26.23											
PC1	18.3597											
M4	28.7148											
W12	34.15											
M5	77.959											
WB2	41.21											
PC9_3	42.97											
B1	22.3											
PC5	82.3056											
WB1	41.66											
W8	6.61											
PC9_4	23.23											
PC11	6.88											
PC10	10.0218											
	1089.59											

example : 100 year allowable flow pond B = 23.33 x 0.025
= 0.584

for Outlet A - the flows are based on existing hydrology

Summary of Pond Target Flows:

Pond	Pond Trib area (ha)	24 hr SCS 100 year Target flow m3/sec	24 hr SCS 50 year Target flow m3/sec	24 hr SCS 25 year Target flow m3/sec	24 hr SCS 10 year Target flow m3/sec	24 hr SCS 5 year Target flow m3/sec	24 hr SCS 2 year Target flow m3/sec	12 hr AES 100 year Target flow m3/sec
Pond A	51.83	0.921	0.727	0.555	0.361	0.24	0.113	0.862
Pond B	23.33	0.584	0.542	0.430	0.300	0.214	0.112	0.487
Pond C	31.35	0.784	0.728	0.579	0.404	0.288	0.151	0.654
Pond D	33.85	0.847	0.786	0.625	0.436	0.311	0.163	0.706
Pond E	11.83	0.296	0.275	0.218	0.152	0.109	0.057	0.247
Pond F	8.00	0.200	0.186	0.148	0.103	0.074	0.039	0.167


POST-DEVELOPMENT CONDITIONS

Schematic storm sewer distribution concepts have been prepared for the subject development as shown on Figure S-7 in Appendix D. Sewer layouts and elevations were established based on existing drainage patterns and below grade rock elevations. The sewer layouts on Figure S-7 are conceptual and are subject to change as the subdivision design evolve.

TOPOLOGY:

The XPSWMM model utilized the Provinces 2018 DEM (Digital Elevation Model) which is Lidar derived. The grid density is 0.5m x 0.5m. We obtained and reviewed topographic survey of the existing site (existing terrain) prepared by MTE, dated February 2021, August 2021. We compared the existing MTE topographic survey to the lidar used in the hydraulic model and find them comparable. It should be noted that the Lidar and MTE data are based on the same vertical datum. The Lidar was adjusted to match the MTE topology. Odan Detech will utilize the adjusted Provincial 2018 DEM (based on Lidar) as the base line existing topology. Refer to Figure 17 for the shaded DEM for the study area.

Figure 16 – Adjusted Provincial 2018 DEM for the study area.



METHODOLOGY

The Floodplain Analysis work will in brief include the following tasks:

1. Review City “Wignell Watershed Hydrology and Hydraulics Report”, EWA Engineers Inc., August 31, 2021.
2. Review “NIAGARA PENINSULA CONSERVATION AUTHORITY FLOOD PLAIN MAPPING WIGNELL DRAIN CITY OF PORT COLBORNE”, NIAGARA PENINSULA CONSERVATION AUTHORITY, August 2011.
3. Compare Province DEM (Lidar derived) to MTE Surveyors Ltd. Adjust the Province DEM to the MTE topo. The adjusted Lidar DEM will become the base line.
4. Request and obtain from City the PCSWMM hydraulic models used by EWA in preparing the Wignell Watershed Hydrology and Hydraulics Report
5. Review the PCSWMM model.
6. Create a 1D/2D model (XPSWMM 2D).
7. Compare existing conditions to that of the Elite Site developed.

The following items will be evaluated via the XPSWMM 1D/2D model:

- ☐ Flood Elevations (Regulatory)
- ☐ **HGL at the subject areas.**
- ☐ Bed shear Calculations
- ☐ Velocity and depth Calculations (Hazard).

HYDRAULIC ANALYSIS:

XPSWMM 1D/2D MODEL:

The model we chose to use is XPSWMM. Many items were transferable. The boundary conditions and 1D nodes were easily copied and pasted from PCSWMM to XPSWMM.

XPSWMM was run with the following scenarios:

1. Existing 0 (Base) - The existing scenario was simulated using the hydrology in the “Wignell Watershed Hydrology and Hydraulics Report”, EWA Engineers Inc., August 31, 2021. The storms run was SCS 24 hr -100, 50, 25, 10, 5, 2-year events and AES 12 hr – 100-year event. The Lake Erie boundary condition was considered as free flow. Please refer to Figure S-5 in Appendix D for the pre-development catchment areas that were modelled.
2. Elite Site Developed 1 - The existing scenario was modified to simulate (add) 6 urban areas flowing to 6 SWM ponds (Elite Site Developed). The storms run was SCS 24 hr -100, 50, 25, 10, 5, 2-year events and AES 12 hr – 100-year event. The Lake Erie boundary condition was considered as free flow. Please refer to Figure S-6 in Appendix D for the pre-development catchment areas that were modelled.
3. Existing 3 Lake boundary modified - The existing scenario was simulated using the hydrology in the “Wignell Watershed Hydrology and Hydraulics Report”, EWA Engineers Inc., August 31, 2021. The Lake Erie boundary condition was 100-year Lake level + 10-year surface runoff event.

4. Elite Site Developed 1 Lake boundary modified - The existing scenario was modified to simulate (add) 6 urban areas flowing to 6 SWM ponds (Elite Site Developed). The Lake Erie boundary condition was 100-year Lake level + 10-year surface runoff event. The pond volumes were modelled based on conceptual pond designs for each pond which can be referenced on Figures S-9 to S-16 in Appendix D.

MODEL:

The Hydrodynamic 2D model utilized is XP2D by Innovyze. XPSWMM 1D is similar to and has the modified EPA SWMM 5 engine. SWMM 5 models can be imported and exported into XPSWMM. XP2D is a computer program for simulating depth-averaged, two and one-dimensional free-surface flows such as occurs from floods and tides. XP2D is based on the computational engine TUFLOW which was originally developed for modelling two-dimensional (2D) flows, and stands for Two-dimensional Unsteady FLOW. XP2D has been dynamically linked (fully integrated) with the XPSWMM 1D solution engine.

2D: TUFLOW HPC's 2D explicit formulation assures unconditional stability. Thus, a reasonable initial time step is 1 to 5 seconds. The program will use the initial time step and divide it by 10 to start the simulation. From that point on the program will adjust.

1D: Finite difference Runge-Kutta explicit scheme. Scheme solves all terms of the St. Venant equations.

1D and 2D schemes automatically switch between upstream and downstream controlled flow regimes to represent shocks.

Prior to embarking on a 2D model routine it is customary practice to create a well-planned work flow so that major items are not missed. The pillar of this work flow is a well conceived Quality Control Check List. See the following check list. It is only checked after the modelling takes place to make sure the report and models are in sync.

Quality Control Check List

Item	Description	Checked
Modeling Log	A modeling log is highly recommended and should be a requirement on all projects. The log may be in Excel, Word or other suitable software. A review of the modeling log is to be made by an experienced modeller. It should contain sufficient information to record model versions during development and calibration, along with observations from simulations. A model version naming and numbering system needs to be designed prior to the modeling. The version numbering system should be reflected in input data filenames to allow traceability and the ability to reproduce an old simulation if needed.	√
File Naming, Structure and Management	A review of the data file management should check: <ul style="list-style-type: none"> files are named using a logical and appropriate system that allows easy interpretation of file purpose and content; a logical and appropriate system of folders is used that manages the files; relative path names to be used for input files (e.g. “..model\geometry.tgc”) so that models are easily moved from one folder to another. documentation of the above in, for example, the projects Quality Control Document and/or Modeling Log. 	√
2D Cell Size	Check whether the 2D cell size is appropriate to reproduce the topography needed to satisfactorily meet the objectives of the study.	√
Topography	The topography review should focus on: <ul style="list-style-type: none"> correct interrogation of DTM; correct datum; modifications to the base data (eg. breaklines) have been checked. Regarding the latter, this is effectively carried out by producing a _zpt GIS check file using Write Check Files. The _zpt layer contains all modifications including any flow constriction adjustments. A DTM can be created from the Zpts using Global Mapper, or other 3D surface software, to aid in the review. Note: Reviewing the elevations in the .2dm file is not appropriate as only the ZH Zpt is represented in the .2dm file (the ZH elevation is not used in the hydrodynamic calculations).	√
Bed Resistance Values	Bed resistance values are to be reviewed by an experienced modeller. The review should focus on checking at least one of: <ul style="list-style-type: none"> Roughness Categories in the Global Database; the grid “Mat” or “Manning_n” values in the grd GIS check file; or specifying weir output using the weir approach. The reviewer should be looking for: <ul style="list-style-type: none"> relative consistency between different land-use (material) types; and values are within accepted calibration values. 	√
Calibration / Validation	Check that the model calibration or validation is satisfactory in regard to the study objectives. Identify any limitations or areas of potential uncertainty that should be noted when interpreting the study outcomes.	√

Mass Conservation	<p>Standard practice is to place PO flow lines at a minimum of several locations through the model. They are typically aligned roughly perpendicular to the flow direction. The locations should include lines just inside each of the boundaries. Other suitable locations are upstream and downstream of key structures, through structures and areas of particular interest.</p> <p>The flows are graphed and conservation of mass checked (i.e. the amount of water entering the model equals the amount leaving allowing for any retention of water in the model). Check that any 1D flow paths crossed by a PO line are also included in the mass check.</p> <p>In dynamic simulations, an exact match between upstream and downstream will not occur due to retention of water, however, examination of the flow lines should reflect this phenomenon.</p> <p>For steady-state simulations, demonstration of reaching steady flow conditions is demonstrated when the flow entering the model equals the flow leaving the model.</p>	√
Free-Over fall & Weir Flow	<p>Especially if Supercritical is set to OFF, the percentage of free-over fall and weir flow velocity points should be checked. The review should seek to check that excessive number of points are not free-overfalling, and if so: that this is in accordance with the expected flow (e.g. weir flow over a levee) – check that the weir option is on if significant weir flow exists; and/or the effect on the overall flow patterns is minimal.</p> <p>The review is best carried out by:</p> <ul style="list-style-type: none"> Monitoring the numbers after “CS” or “FO” on the screen or in the .tif file Specifying flow regime output to generate the _R.dat file. This file shows the flow regime. <p>The presence of significant areas of supercritical and/or weirs can be acceptable in large areas of sheet flow. However, care should be taken in interpreting the flow behavior in these areas, particularly if the flow is supercritical as complex hydraulic processes (e.g. hydraulic jumps, surcharging against buildings) can occur.</p> <p>Typically, most supercritical and weir flow occurs:</p> <ul style="list-style-type: none"> around the edge of a model where it is wetting and drying and has little influence over the general flow behavior; or down steep slopes or over significant drops (eg. over a levee). 	√
Hydraulic Structures	<p>Head losses through a structure need to be validated through:</p> <ul style="list-style-type: none"> Calibration to recorded information (if available). Crosschecked using desktop calculations based on theory and/or standard publications (eg. Hydraulics of Bridge Waterways). Crosschecked with results using other hydraulic software (e.g. HEC-RAS). <p>Simple checks can be made by calculating the number of dynamic head losses that occur and checking that this in accordance with that expected</p> <p>It is important to note that contraction and expansion losses associated with structures are modeled very differently in 1D and 2D schemes. 1D scheme rely on applying form loss coefficients, as they cannot simulate the horizontal or vertical changes in velocity direction and speed. 2D schemes model these horizontal changes and, therefore, do not require the introduction of form losses to the same extent as that required for 1D schemes. However, 2D schemes do not model losses in the vertical or fine-scale horizontal effects (such as around a bridge pier) and, therefore, may require the introduction of additional form losses. See Syme 2001b for further details.</p>	√
Eddy Viscosity	Check that the eddy viscosity formulation and coefficient is appropriate	√

Following on pg 38 shown on Figure 18, is the existing condition XPSWMM model. The XPSWMM model was built from the Provinces 2018 DEM which is Lidar derived. The raw data was imported into Global Mapper (Geospatial software) where it was reviewed and edited if necessary. A digital terrain model was created in Global Mapper. Through Global Mapper a grid file (XYZ) file was created and sent to XPSWMM. XPSWMM then creates the DTM. The DTM still satisfies the theory that a good 2D model should contain for each 2D cell at least 2 vertices on average.

TIME STEP:

As a rule, the time step is typically half the cell size. Typical 2D time steps are $\frac{1}{2}$ the cell size (XPSWMM 2D manual). For steep models with high Froude numbers and supercritical flow, smaller time steps may be required. For this site it will not be an issue (this Site is relatively flat).

If the model is operating at high Courant numbers (>10), sensitivity testing with smaller time steps to demonstrate no measurable change in results should be carried out. The occurrence of high mass errors is also an indicator of using too high a time step. It is recommended that the time step of the 2D engine be equal to or an integer multiple of the time step of the 1D calculations.

We have adapted the following time steps to start:

1D model	1.0 sec
2D model	1.0 sec

XP2D is finite volume based, explicit formulation. As mentioned above the program will use the initial time step and divide it by 10 to start the simulation. From that point on the program will adjust. The above noted criteria are met and there are no stability issues with the model.

CELL SIZE:

The cell sizes of 2D domains need to be sufficiently small to reproduce the hydraulic behavior. Based on review of benchmark studies, experience and consultation with Innovyze the chosen **Grid size of 2.5 m** is adequate. It has enough resolution to capture local ditches, and space between buildings.

CELL ROUGHNESS:

Refer to Figure 18 for the grid roughness. The grid roughness was set to a **Manning n of 0.050** for the existing natural areas and residential lawns. There are no urban areas where the 2D grid is provided. Therefore, a single manning n is provided. The Developed Elite site was modelled as a 1D system (hydrology nodes, to storage node, with control structure) out letting to a node linked to a 2D cell.

HYDROLOGY PARAMETERS:


The existing XPSWMM hydrology model is the same as the PCSWMM model. Refer to Table 6 for the post developed (Elite Site developed) hydrology parameters. The Post Developed model has urban runoff and the existing tributaries are subdivided.

Table 6. Post Development hydrology parameters

Name	Subcatchment	Impervious Area depression storage (mm)	Pervious Area depression storage (mm)	Area ha	Width m	Slope m/m	Impervious Percentage %	Infiltration Reference	Hydrology Methods	Normal method length (m)	Normal method width (m)	measured length (m)	new width (m)
J1	1	10	5	28.75	288	0.00	4.5	M1	SWMM	437.8	328.3	280.0	513.3
J10	1	10	5	5.44	60	0.01	85.0	PC9_4	SWMM	190.5	142.8	280.0	97.2
J12	1	10	5	100.60	680	0.01	4.5	W10	SWMM	818.9	614.2	280.0	1796.4
J15	1	10	5	15.05	132	0.00	3.0	PC7	SWMM	316.8	237.6	570.0	132.0
J16	1	10	5	7.64	50	0.00	1.0	PC8	SWMM	225.7	169.3	775.0	49.3
J17	1	10	5	7.96	153	0.00	4.5	PC5	SWMM	230.4	172.8	280.0	142.1
J18	1	10	5	1.98	40	0.00	55.0	PC10	SWMM	114.9	86.2	280.0	35.4
J19	1	10	5	63.43	906	0.00	0.0	PC4-QE1	SWMM	650.3	487.7	280.0	1132.7
J2	1	10	5	26.53	420	0.00	4.5	M2	SWMM	420.5	315.4	280.0	473.7
J20	1	10	5	66.06	660	0.00	0.0	PC3-QW1	SWMM	663.6	497.7	280.0	1179.6
J21	1	10	5	19.34	198	0.01	4.5	PC1	SWMM	359.1	269.3	280.0	345.4
J21	2	10	5	36.60	374	0.00	4.7	PC2	SWMM	493.9	370.5	280.0	653.5
J22	1	10	5	58.30	511	0.01	4.5	W1	SWMM	623.4	467.6	280.0	1041.0
J23	1	10	5	77.96	488	0.01	4.5	W2	SWMM	720.9	540.7	280.0	1392.1
J24	1	10	5	18.36	275	0.00	4.5	W12	SWMM	349.9	262.4	280.0	327.9
J24	2	10	5	41.66	495	0.00	4.5	W7	SWMM	527.0	395.3	280.0	743.9
J24	3	10	5	10.02	250	0.00	4.5	W82	SWMM	258.5	193.9	280.0	179.0
J25	1	10	5	82.31	986	0.00	4.5	W6	SWMM	740.7	555.6	280.0	1469.8
J26	1	10	5	22.30	354	0.00	4.5	W5	SWMM	385.6	289.2	280.0	398.2
J27	1	10	5	34.15	491	0.00	4.5	W14	SWMM	477.1	357.9	280.0	609.8
J28	1	10	5	41.21	330	0.00	4.5	W3	SWMM	524.2	393.1	280.0	735.9
J29	1	10	5	6.61	220	0.00	4.5	W8	SWMM	209.9	157.4	280.0	118.0
J29	2	10	5	6.88	260	0.00	4.5	WB1	SWMM	214.2	160.6	280.0	122.9
J30	1	10	5	12.04	502	0.01	4.5	W9	SWMM	283.3	212.5	280.0	214.9
J32	1	10	5	8.79	239	0.01	4.5	PC9_3	SWMM	242.0	181.5	280.0	156.9
J4	1	10	5	18.79	470	0.01	4.5	M4	SWMM	353.9	265.4	280.0	335.5
J5	1	10	5	16.71	597	0.01	4.5	M5	SWMM	333.7	250.3	280.0	298.3
J6	1	10	5	8.32	201	0.00	5.0	B1	SWMM	235.5	176.6	280.0	148.6
J7	1	10	5	41.95	411	0.01	4.5	M3	SWMM	528.8	396.6	280.0	749.1
J8	1	10	5	26.23	1380	0.03	4.5	W11	SWMM	418.2	313.6	280.0	468.4
J88	1	10	5	3.65	37	0.00	45.0	PC11	SWMM	156.0	117.0	280.0	65.2
J15.1.1	1	10	5	20.84	280	0.00	4.5	PC6	SWMM	372.7	279.5	280.0	372.1
Node 56-1	1	2	5	2.00	86.6	0.02	60.0	urban	SWMM	115.5	86.6	280.0	35.7
J87	1	10	5	28.72	342.0	0.004	4.5	W13	SWMM	437.5	328.1	280.0	512.8
Node84	1	2	5	23.33	295.8	0.01	54.0	urban	SWMM	394.4	295.8	280.0	416.6
Node88	1	2	5	51.83	440.9	0.01	43.0	urban	SWMM	587.8	440.9	280.0	925.5
Node92	1	2	5	31.35	342.9	0.01	66.0	urban	SWMM	457.2	342.9	280.0	559.9
Node96	1	2	5	8.00	173.0	0.01	70.0	urban	SWMM	231.0	173.2	280.0	142.9
Node100	1	2	5	33.85	400.0	0.01	62.0	urban	SWMM	475.0	356.3	280.0	604.4
Node108	1	2	5	11.83	210.6	0.01	70.0	urban	SWMM	280.8	210.6	280.0	211.2
Node109	1	10	5	15.79	243.3	0.01	4.0	PC7	SWMM	324.4	243.3	280.0	281.9
				1143.13									

Note the two quarry areas J19 and J20 are included in the above parameters, however the areas were turned off in the simulation. The CN curve number of 83 was used in the urban infiltration model. The area = 1143.13 is very close to the Wignell Drain area of 1089.58 ha + 51.83 ha (flow area to south Welland, node88) = 1141.41 ha (existing conditions).

Figure 17 – XPSWMM Global Existing model



Legend: Δ - storage node, \circ -node/MH, \rightarrow Link (pipe), \rightarrow dummy link, \square inactive node
 \rightarrow Link culvert, \rightarrow Link open channel, \rightarrow Link orifice and or weir

Grid Manning $n = 0.05$

Figure 18 – XPSWMM existing model showing Tributary areas and node links




Figure 19 – XPSWMM Global Elite Site Developed model




Figure 20 – XPSWMM Elite Site Developed model showing Tributary areas and node links






Figure 21 – Close up of urbanized XPSWMM Elite Site Developed model



DISCUSSION OF XP2D MODEL:

The following items are in no particular order.

- 1) The PCSWMM model by EWA was utilized in the XPSWMM model. The red square nodes shown in Figure 18 above are nodes from PCSWMM representing the nodes at the end of the links. In XPSWMM we replaced the Wignell Drain links with a 2D mesh. Thus, the red squares are the XPSWMM nodes turned off. In addition, the links were turned off. Only select channels and culvert crossings were modelled.
- 2) The hydrology nodes (where run-off is directed) are linked to 2D mesh if the runoff is in the valley area (Wignell drains). If connected to pipes, they are not linked to 2D mesh.
- 3) The pond outlet nodes for ponds B to F are linked to the 2D mesh at the creek outfall. Pond A has no 2D mesh.
- 4) To accept flow from a 1D domain to a 2D domain or vice versa the nodes must be linked to the 2D mesh.
- 5) Culvert crossings utilize entrance loss of 0.5 and exist loss of 1.0.
- 6) Culvert crossing utilize manning n as per the NPCA HEC-RAS model (variable with depth)
- 7) HGL levels at select locations are retrieved via points 1 to 13. The points are in identical locations in the existing and post models.
- 8) There are no celerity issues with the model.
- 9) The continuity error is excellent.
- 10) There were no error messages from the analysis.
- 11) The HGL maximum at any given point in the system is the most useful result. The animation of the flow with time, best shows how the upper flows are attenuated through the system and the effect of downstream tail water if it exists.
- 12) Hydro-dynamic models provide the most accurate, reliable and defensible representation of flows in the collection system. They account for varying inflows, non-coincident peak flows, in system storage, hydrograph attenuation, and tail and backwater effects. In addition, the integration with a 2D model allows accurate spill over calculations of the Flood plain along with the attenuation effects of the spill.
- 13) **The following are the key items affecting HGL in dynamic models:**
 - pipe and or channel volume,
 - length of flow, spill and volume in the spill area,
 - runoff hydrograph (length in time and volume),
 - timing of peaks which are controlled by the above.
- 14) The analysis is based on clean channels. No percentage blocked.

MODELLING RESULTS:

FLOOD SCENERO (Peak Flows)

The following Table 7 is a summary of the storage volumes required in the proposed ponds to control the 100-year storm to pre-development levels. Conceptual pond designs for each pond showing conceptual elevations can be referenced on Figures S-9 to S-16 in Appendix D.

Table 7. Required Storage Volumes Elite Site Developed						
BLOCK ID	Upstream Contributing Area (ha)	100 Year Storage Required (m3)	100 Year HGL - in pond (m)	100 Year Storage Provided at 2.0 m depth (m3)	Top of Pond elevation (m)	Pond Freeboard (m)
Pond A	51.83	24,908	179.37	32,453	179.78	0.41
Pond B	23.33	13,777	178.83	25,792	179.70	0.87
Pond C	31.35	17,978	179.29	22,161	179.60	0.31
Pond D	33.85	20,467	178.52	25,508	178.85	0.33
Pond E	11.83	7,785	178.63	13,383	179.30	0.67
Pond F	8.00	5,596	179.24	8,726	179.80	0.56

Refer to Table 8 below for the comparison of peak outflows for the ponds. Note, existing is the target flow from the XPSWMM existing model (see summary of pond target flows) while the developed heading is the XPSWMM post model results from the ponds.

Table 8. Comparison of Pre-Development and Developed Site Pond flows.													
Storm Event	Storm Type	Peak Flow Rate (m³/s)											
		Pond A		Pond B		Pond C		Pond D		Pond E		Pond F	
		Existing Target flow	Developed	Existing Target flow	Developed	Existing Target flow	Developed	Existing Target flow	Developed	Existing Target flow	Developed	Existing Target flow	Developed
2 Year	24Hr SCS	0.113	0.070	0.112	0.070	0.151	0.122	0.163	0.112	0.057	0.031	0.039	0.000
5 Year	24Hr SCS	0.240	0.197	0.214	0.099	0.288	0.298	0.311	0.151	0.109	0.090	0.074	0.003
10 Year	24Hr SCS	0.361	0.372	0.300	0.129	0.404	0.412	0.436	0.188	0.152	0.117	0.103	0.029
25 Year	24Hr SCS	0.555	0.605	0.430	0.198	0.579	0.541	0.625	0.334	0.218	0.148	0.148	0.063
50 Year	24Hr SCS	0.727	0.739	0.542	0.252	0.728	0.623	0.786	0.460	0.275	0.167	0.186	0.088
100 Year	24Hr SCS	0.921	0.851	0.584	0.290	0.784	0.686	0.847	0.562	0.296	0.185	0.200	0.110
100 Year	12Hr AES	0.862	0.879	0.487	0.304	0.654	0.658	0.706	0.578	0.247	0.184	0.167	0.117

SCENARIO 1 Existing Conditions (Base)

Figure 22 - XPSWMM depth MAP (100year) - site undeveloped existing flows




Figure 23 - XPSWMM depth MAP (50year) - site undeveloped existing flows




Figure 24 - XPSWMM depth MAP (25year) - site undeveloped existing flows




Figure 25 - XPSWMM depth MAP (10 year) - site undeveloped existing flows




Figure 26 - XPSWMM depth MAP (5 year) - site undeveloped existing flows




Figure 27 - XPSWMM depth MAP (2 year) - site undeveloped existing flows




Figure 28 - XPSWMM hazard MAP (100year) - site undeveloped existing flows






Figure 29 - XPSWMM bed shear MAP (100 year) - site undeveloped existing flows



The above map is the 100-year bed shear. The maximum is 114 Pa. anywhere in the system.

Figure 30 - XPSWMM bed shear MAP (2 year) - site undeveloped existing flows



The above map is the 2-year bed shear. The maximum is 50 Pa. anywhere in the system.

SCENARIO 2 – Elite Site developed

Figure 31 - XPSWMM depth MAP (100year) - Elite Site Developed




Figure 32 - XPSWMM depth MAP (50year) - Elite Site Developed




Figure 33 - XPSWMM depth MAP (25year) - Elite Site Developed




Figure 34 - XPSWMM depth MAP (10 year) - Elite Site Developed




Figure 35 - XPSWMM depth MAP (5 year) - Elite Site developed




Figure 36 - XPSWMM depth MAP (2 year) - Elite Site developed




Figure 37 - XPSWMM hazard MAP (100 year) - Elite Site developed






Figure 38 - XPSWMM bed shear MAP (100 year) - Elite Site developed



Note, the 100 year maximum in the developed site is less than the existing conditions.

Figure 39 - XPSWMM bed shear MAP (2 year) - Elite Site developed



Note, the 2-year maximum in the developed site is less than the existing conditions.

POINT HEAD PLOT



The points are locations where HGL are retrieved. See Table 9 for points summary. See below for the section plots. It should be noted that the geospatial locations of these points and sections are identical for existing conditions scenario and Elite Site developed scenario.


Table 9 Summary of hydraulic effects existing and Elite Site Developed

	100-year 24 hr SCS		50-year 24 hr SCS		25-year 24 hr SCS		10-year 24 hr SCS		5-year 24 hr SCS		2-year 24 hr SCS	
	HGL (m)											
Location	existing	Developed	existing	Developed	existing	Developed	existing	Developed	existing	Developed	existing	Developed
Point 1	177.08	177.06	176.94	176.95	176.80	176.83	176.60	176.61	176.50	176.52	176.35	176.36
Point 2	177.20	177.18	177.10	177.14	177.03	177.08	176.96	177.00	176.88	176.92	176.74	176.76
Point 3	177.44	177.45	177.40	177.43	177.36	177.40	177.30	177.34	177.24	177.27	177.08	177.10
Point 4	177.77	177.90	177.74	177.82	177.68	177.74	177.58	177.66	177.50	177.62	177.40	177.59
Point 5	177.96	178.02	177.94	177.93	177.92	177.96	177.90	177.91	177.85	177.86	177.78	177.78
Point 6	177.44	177.39	178.41	178.37	178.40	178.36	178.38	178.32	178.32	178.30	178.22	178.22
Point 7	178.69	178.70	178.66	178.69	178.62	178.66	178.57	178.62	178.54	178.59	178.44	178.54
Point 8	179.05	179.04	178.98	178.99	178.90	178.90	178.78	178.79	178.68	178.70	178.54	178.60
Point 9	175.74	175.74	175.69	175.69	175.67	175.67	175.64	175.64	175.60	175.59	175.49	175.49
Point 10	175.73	175.74	175.68	175.68	175.63	175.64	175.55	175.55	175.47	175.48	175.40	175.40
Point 11	175.73	175.73	175.68	175.68	175.63	175.63	175.54	175.54	175.45	175.46	175.36	175.35
Point 12	175.69	175.68	175.62	175.61	175.54	175.54	175.43	175.43	175.35	175.35	175.27	175.27
Point 13	175.53	175.48	175.45	175.44	175.38	175.37	175.25	175.25	175.16	175.16	175.00	175.00

Note, essentially the existing and Elite Developed Site HGL are the same.


SECTION PLOTS

The following map shows the locations of profile plots for existing and proposed models.




Profile 1 100 year 24 hr SCS

Existing




Elite Site Developed




Profile 2 100-year 24 hr SCS

Existing




Elite Site Developed




Profile 3 100-year 24 hr SCS

Existing



Elite Site Developed



EROSION REVIEW:

The bed shear stress is calculated as follows in XP2D:

$$\tau_{bed(metric)} = \frac{\rho g v^2 n^2}{y^{1/3}}$$

where:

ρ = Density

g = Gravity

v = Velocity

n = Manning's n

y = Depth

Units are in N/m²

Reproduced from HEC-15, FHWA-NHI-01-021 August 2001, Urban Drainage Design Manual, the following are the recommended shear stress as per vegetative cover.

Lining Category	Type	Permissible Unit Shear Stress (Pa)
Vegetative	Class A	177.2
	Class B	100.6
	Class C	47.9
	Class D	28.7
	Class E	16.8

Refer to the bed shear maps above for the calculated unit shear stress. Majority of the cells in the landscaped area and the drain area have bed shear stress less than 114 N/m². Note this is for the 100-year Storm. The 2 year storm bed shear maps indicates a bed shear of 50 N/m² in the existing condition and 39 N/m² in the developed condition (maximum). This is well within the permissible range for a well vegetated area.

The objective is to not increase the erosion forces in the receiving natural stream. The MOE outlined an interim approach in 1994 and updated it in the Stormwater Management Planning and Design Manual (MOE, 2003). This updated approach consists of either a detailed design approach or a simplified design approach that is currently being improved to address inadequacies. Accordingly, it is recommended that the general approach be followed as outlined in the Stormwater Management Planning and Design Manual (MOE, 2003). This consists of designing SWM ponds to include active storage for the runoff from a 25 mm storm, followed by a check on erosion velocities in the downstream receiver. Quantity control to detain and release the 25mm, 4-hour Chicago design storm over a 24-hour period shall be provided for all receiving systems that are demonstrated to be stable watercourses or for proposed development that comprise less than 10% of the total area that drains to the receiving system.

Note, the shear bed method in 2D modelling is quickly becoming the method of choice due to testing that shows shear stress is a better indicator of erosion than velocity.

Refer to Table 10 for the comparison of existing to developed flows (target flows)

No.	Location description or crossing	S-4	Killaly culvert crossing east of Lorraine Road
S-1	Hwy # 3 culvert crossing west branch	S-5	Snider culvert crossing just north of Friendship Trail (former CNR)
S-2	Hwy # 3 culvert crossing east branch	S-6	Friendship trail culvert crossing adjacent to Snider Road west side
S-3	Killaly culvert crossing west of Snider Road	S-7	Outlet to Lake

Table 10 XPSWMM comparison of Outflow – existing (target) and redeveloped

Storm Event Storm Type	Target Peak Flow Rate (m³/s)																				
	S-1			S-2			S-3			S-4			S-5			S-6			S7		
	Existing	Developed	PCSWMM	Existing	Developed	PCSWMM	Existing	Developed	PCSWMM	Existing	Developed	PCSWMM	Existing	Developed	PCSWMM	Existing	Developed	PCSWMM	Existing	Developed	PCSWMM
2 Year 24Hr SCS	0.439	0.440	0.406	0.730	0.730	0.764	1.070	1.044	1.169	0.685	0.690	1.184	1.025	0.975	1.803	1.026	1.007	2.923	0.479	0.462	2.908
5 Year 24Hr SCS	0.794	0.799	0.750	1.215	1.209	1.256	1.787	1.804	2.156	1.554	1.546	2.806	1.946	1.834	4.266	1.954	1.896	6.375	1.046	1.041	6.580
10 Year 24Hr SCS	1.054	1.064	1.009	1.591	1.595	1.671	2.357	2.501	2.975	2.326	2.320	4.276	2.521	2.358	5.189	2.531	2.442	7.933	1.484	1.435	8.521
25 Year 24Hr SCS	1.401	1.405	1.370	2.160	2.168	2.328	3.157	3.397	4.220	3.422	3.419	5.018	2.663	2.626	5.719	3.335	3.264	7.933	1.781	1.746	9.380
50 Year 24Hr SCS	1.646	1.654	1.655	2.651	2.653	2.906	3.873	4.013	5.273	4.239	4.243	5.294	2.694	2.654	6.081	3.848	3.869	7.933	1.966	1.920	9.791
100 Year 24Hr SCS	1.903	1.904	1.951	3.157	3.157	3.557	4.626	4.533	5.719	4.994	5.002	5.629	2.698	2.652	6.481	4.335	4.339	7.933	2.179	2.146	10.00
100 Year 12Hr AES	0.606	0.606	-	1.976	1.976	-	4.043	4.026	-	4.628	4.637	-	2.701	2.699	-	4.020	4.101	-	1.774	1.746	-


Note, PCSWMM had approximately 0.53 m3/sec from the quarry area which should not be included.

SCENERIO 3 Existing conditions - Lake boundary modified

In this scenario the Lake Erie boundary condition was 100-year Lake level + 10-year surface runoff event. The outfall was raised to **75.10 m** to represent the Lake 100-year level + wave setup. At the control structure a flap gate was added since the control structure has sluice gates. Only the 10-year storm was run.

In order to keep probabilities of lake levels and surface runoff real the scenarios will be as follows: 10-year surface and 100-year Lake Level and vice versa. Many Conservation Authorities and MNR use this criterion.

Figure 40 - XPSWMM depth MAP- Existing – 100 yr Lake – 10 yr storm



SCENERIO 4 Elite developed - Lake boundary modified

In this scenario the Lake Erie boundary condition was 100-year Lake level + 10-year surface runoff event. The outfall was raised to **75.10 m** to represent the Lake 100-year level + wave setup. At the control structure a flap gate was added, since the control structure has sluice gates. Only the 10-year storm was run.

Figure 41 - XPSWMM depth MAP- Elite developed – 100-yr Lake – 10-yr storm




Table 11 Summary of Lake effects - hydraulic effects existing and Elite Site Developed

	10-year 24 hr SCS 100 yr Lake		10-year 24 hr SCS Free flow	
	HGL (m)			
Location	existing	Developed	existing	Developed
Point 1	176.60	176.61	176.60	176.61
Point 2	176.96	177.00	176.96	177.00
Point 3	177.30	177.34	177.30	177.34
Point 4	177.58	177.66	177.58	177.66
Point 5	177.90	177.91	177.90	177.91
Point 6	178.38	178.32	178.38	178.32
Point 7	178.57	178.62	178.57	178.62
Point 8	178.78	178.79	178.78	178.79
Point 9	175.64	175.64	175.64	175.64
Point 10	175.55	175.55	175.55	175.55
Point 11	175.54	175.54	175.54	175.54
Point 12	175.44	175.43	175.43	175.43
Point 13	175.30	175.30	175.25	175.25

Notes:

1. Based on Table 11 the only area effected by the high Lake water is point 13 near the Lake.
2. The Elite Development does not appreciably affect the area when the Lake is high.
3. The probability of lake levels and surface runoff rare events concurring are unlikely, thus the scenario of 10-year surface and 100-year Lake Level is more realistic.

REVIEW OF INGRESS/EGRESS AND RISK ASSESSMENT

INGRESS/EGRESS

Source: (Ontario MNR Technical Guide – River and Streams Systems: Flooding Hazard Limits, 2002).

MNR Technical Guide Appendix 5 page 28 states the question of safety for the passage of vehicles can be subdivided into:

- Flood depth and velocity considerations affecting egress of private vehicles from flood proofed areas;
- Flood depth and velocity affecting access of private and emergency vehicles to flood proofed areas.

The highest priorities for access to emergency vehicles should be given to police, ambulance and fire services, especially where evacuation is a distinct possibility in areas surrounded by flooding.

Access to the proposed development will be provided via streets that are not flooded. Note, Snider Road is the only street presently flooded. We are suggesting that Snider Road will be raised and a new culvert placed at the drain location to pass a 100-year storm. This will make Snider Road a non-flooded road.

Private Vehicle: allowable depth 0.3 m and velocity of 3.0 m/sec, hazard 1.0 m²/sec

Therefore, Private vehicle ingress/egress is not an issue.

Emergency Vehicle: allowable depth 0.9 m and velocity of 4.5 m/sec for firefighting and depth 0.3 m and velocity of 3.0 m/sec for police and ambulance and hazard of 1.0 m²/sec (MNR Technical Guide).

Therefore, Private vehicle ingress/egress is not an issue.

Pedestrian: allowable depth 0.8 m and velocity of 1.7 m/sec and max hazard of 0.40 m²/sec (MNR Technical Guide).

Therefore, Pedestrian ingress/egress is not an issue.

RISK ASSESSMENT:

Application of the 2 x 2 rule (see Ontario MNR Technical Guide – River and Streams Systems: Flooding Hazard Limits, 2002) used in the assessment of potential loss of life. The 2 x 2 rule defines that people would be at risk if the product of the velocity and the depth (HAZARD) exceeded 0.40 square metres per second or if velocity exceeds 1.7 metres per second or if depth of water exceeds 0.8 metres. (Source MNR flood plain management).

Based on the above the risk is **low**.

WATER QUALITY

The Subwatershed Study & SWMP Implementation Document establishes the required guidelines for implementing stormwater quality for the proposed development. The requirements for Water quality are as follows.

“Control pollutant loadings in accordance with current MOE guidelines. Enhanced Level 1 protection as defined in the 2003 Stormwater Management Planning & Design Manual – reduce average long term annual load of suspended sediment by 80% or better. Accomplish through the use of LID source and conveyance controls.”

Stormwater Source Control Policy for Industrial, Commercial and Institutional (ICI) Land Uses by NPCA is guide.

In order to achieve water quality for the proposed development each site will be required to implement the above measures to achieve an Enhanced Level 1 Protection of 80% removal of total suspended solids prior to discharge into downstream outlets.

In order to achieve the required water quality for each development the following methods can be considered at the detailed design stage for the subdivision. The following provides values established and generally accepted throughout the province for use of various TSS removal techniques.

Total Suspended Solid Removal Method & Removal Efficiency	
Removal Method	Removal Efficiency
Rooftop	80%
Grassed Swale (with Perforated Pipe)	80%
Grass Swale (no perforated Pipe)	50%
Soakaway & Infiltration Systems	70-90%
Chambers (with Infiltration)	70-90%
Bio retention	80%
Dry Swale	80%
Permeable Pavers (with Storage Bed)	80%
OGS (Oil/Grit Separator)	50%-80%
CB Shield	* 50%
Wet Pond	** up to 90% TSS removal if extended detention is used

* - Based on Table provided by Manufacturer.

** - New Jersey Department of Environmental Protection

This may be due to constraints such as limited landscape space available throughout the site for implementing LID's, underlying soils conditions and conductivity to LID's, groundwater conditions and other factors that can limit the use of LID's. All reasonable attempts should be made during the detailed design stage to provide for the use of LIDs to enhance water quality measures.

The efficiencies of Low Impact Development Strategies are variable dependent on the maintenance and loading from the site usage. The above Table values are based on the generally accepted removal efficiencies based on the technique implemented.

In order to ensure the removal of oils each outlet will require an oil grit separator or method of removing oil spills prior to discharging to the downstream outlet and receiving water course.

VOLUME CONTROL AND WATER BALANCE:

Improve quality of drainage discharging to each outlet from that of existing conditions; Enhanced (Level 1), as per City, Region and NPCA Criteria. Reduction of the Total Suspended Solids (TSS) released to an enhanced level equal to 80% TSS removal, based on the MOECC 2003 criterion. Approach will be a train treatment.

LIDS:

The following LID methods are possible.


- ☐ Imbrium Filterra Bioretention System
- ☐ Silva Cells
- ☐ Soak away pits
- ☐ Bio swales
- ☐ others

We believe the following can be adapted for the SWM quality/water balance component:

1. Wet ponds as detailed in this report
2. Silva Cells or Imbrium Filterra Bioretention System on the roads if City will accept.
3. Soak away pits in the park area.
4. Bioswales if landscaped areas can accept.
5. Irrigation reuse.
6. Roof flow capture via barrels for reuse.

Imbrium Filterra Bio retention System

This is an appropriate method for water quality treatment in a train treatment environment. Storm water runoff enters the Filterra system through a curb-inlet opening and flows through a specially designed filter media mixture contained in a landscaped modular container. The following photos show the installed Filterra unit and a section through the unit.



Silva Cells

The Silva Cell is a modular suspended pavement system that uses soil volumes to support large tree growth and provide powerful on-site storm water management through absorption, evapotranspiration, and interception. The system is typically installed under pavement applications and can be configured in several different ways:

Streetscapes

Adjacent to or under sidewalks
Between buildings and streets.

Parking Areas


Under parking stalls adjacent
to medians or islands.

Public Spaces

Under plazas, promenades, courtyards, or other public spaces at office buildings, museums, schools, and transit centers

The Region of York is using Silva Cells on the widening and reconstruction of Yonge Street.

The following detail is a typical Silva Cell application.



WATER BALANCE/GROUNDWATER

Refer to report by EXP Hydrogeologist “ Preliminary Hydrogeological and Water Balance Investigation”, Killaly street East, Port Colborne Ontario.

The following is the summary from that report. Note, there is 33,161 m³ deficient in the infiltration rate from pre to post conditions. The Elite site will require to infiltrate 33, 161 m³ of rainfall on an annual basis.

Killaly Street East, Port Colborne, ON
BRM-21000726-A0

Appendix E-4 Summary of Pre and Post-Development Water Balance (Unmitigated)

6. Comparison of Pre-Development and Post-Development Un-Mitigated

	Precipitation (cu.m.)	Actual Evapotranspiration (cu.m.)	Run-off (cu.m.)	Corrected Infiltration Rate for Areas with Shallow Groundwater Table (cu.m.)
Pre-Development	1,490,625	868,758	423,299	198,568
Post Development	1,490,625	579,163	746,057	165,406
Pre-development Infiltration Rate				133.3
Post-development Infiltration Rate Un-Mitigated				111.1
Deficit Post Development Un-Mitigated				33,161

Criteria

Criteria for storm water balance, retention and low-impact-development (LID) is provided for the City of Port Colborne and by the Niagara Peninsula Conservation Authority (NPCA). The NPCA provides criteria in their manual *Niagara Peninsula Conservation Authority Stormwater Management Guidelines* (March 17, 2010).

Stormwater Volume Control Requirements in the NPCA manual provides criteria. The criteria applying to this development is generally described as follows:

- Any major development or disturbance that reconstructs 0.5 Ha of impervious surfaces are subject to storm water volume control criteria.
- Storm water volume reduction (storm water retention) may include such techniques as infiltration, reuse, rainwater harvesting, canopy interception, evapotranspiration and/or additional techniques.
- Redevelopment volume control – nonlinear redevelopment projects meeting the foregoing criteria shall capture and retain/treat on-site the runoff from a pre to post water balance analysis event from the new and/or fully reconstructed impervious surfaces.
- The retained runoff is to be dispersed on-site by the acceptable measures (above) in 48 hours.

The proposed development which comprises approximately 148.93 Ha of which 53.94 ha of impervious surface, is subject to the storm water balance/retention requirements. It is demonstrated as follows that the criteria can be addressed in the proposed development principally by infiltration, with additional retention provided by irrigation (evapotranspiration) and rainwater harvesting.

Based on the EXP report the deficit is 22.3 mm/a rainfall event, falling on the proposed new and reconstructed impervious surfaces, will generate the following storm water retention volume requirement.

Area of impervious surfaces = $53.94 \times 10000 = 539,400 \text{ m}^2$

$$\text{Required Stormwater Retention Volume} = 539,400 \text{ m}^2 \times 22.3 \text{ mm} = 12,029 \text{ m}^3$$

Retention Strategy

It is proposed to principally retain the foregoing 12,029 m³ by infiltration galleries whereby the foregoing volume of water will percolate into the underlying soil.

The locations and footprint available for infiltration galleries have been functionally considered in potential locations for infiltration galleries with a total footprint of 4.20 Ha. The infiltration footprint would be located within lands planned to be allocated for parks such that all infiltration galleries will be controlled. The footprints will need to be sized such that there is a minimum 5m setback (OBC latest edition) from the potential location of any buildings (above- or below-ground) on the adjacent development blocks.

The design criteria for infiltration galleries comprises the following factors. The province of Ontario's *Stormwater Management Planning & Design Manual* (2003) provides design criteria for infiltration galleries. The criteria are identified and addressed as follows.

- Underlying groundwater table elevation
- Criteria: the MECP states that the groundwater table or bedrock elevation should be 1.0m below the bottom of infiltration galleries.
- Design: A Hydrogeological Investigation was prepared by EXP, Dated September 15, 2021. Table 3.1: *Summary of measured groundwater elevations in Monitoring Wells* from 14 wells. The observed groundwater is typically 0.4 to 3m below existing grade. This is sufficient depth below-grade in which to install an infiltration gallery with 1m clear above the groundwater/bedrock. If necessary, the landscaped space in which the infiltration galleries will be installed can be graded such that there is sufficient cover above the stable groundwater table in which to install an infiltration gallery.
- Percolation rate of underlying soils. The MECP states that infiltration galleries should only be proposed where the percolation rate of receiving soils is greater than 15mm. Infiltration gallery footprints are to be designed considering percolation rates.
- EXP has not provided infiltration rate. We are assuming the MOE 2003 minimum of **15mm/hr** in the following analysis – this has been applied in the following infiltration gallery design calculations.

- Drain down time of infiltration galleries.

Criteria: The MECP and NCPA manuals state that infiltration galleries should drain-down in 48 hours following the design storm event.

Design: A drain-down time of 48 hours has been applied in the following infiltration gallery calculations.

Shown below is a sample infiltration gallery sizing calculation showing that the infiltration gallery footprint required to drain-down a retention volume of 12,029m³ (above) within 48 hours is 41,766m², which aligns with the potential infiltration gallery areas within the site mentioned above (42,000m²). This is less than the required footprint, therefore this is preliminarily a feasible means of addressing the storm water retention requirement in-full.

It is possible that in the future design, refinement of the infiltration galleries placement yields smaller available footprints than has been preliminarily identified above. In such a case, the water balance volume can be achieved by other forms such as irrigation and other forms of greywater reuse such as roof capture barrels.

INFILTRATION GALLERY CALCULATION									
PROJECT: Elite - Killaly Street East - Port Colborne									
PROJECT No. : 21247									
Location of infiltration gallery: TBD									
						DESCRIPTION			
						A = 1,000V / (PnΔt)			
						UNIT			
d = PΔt/1000						P=	15	mm/hr	Where:
						Δt =	48	hr	
d =	0.72	m							
						n=	0.40	-	A = Filter bed surface area (m2) V = Water volume (m3) Δt = time to drain (hr) n = void space ratio for aggregate used (note: void space ratio of 0.4 to be used) P = soil percolation rate mm/hr d = PΔt/1000 Atrib = pervious area contributing runoff Where: d = maximum soak-away depth (m) P= infiltration rate for native soils (mm/hr) Δt = time to drain (hr) Af = Filter bed surface area provided (m2) Vpit req'd = V/n Vpit provided = L x W x d L = length of pit (m) W = width of pit (m) d = depth of pit (m)
V=	12029	m3	Atrib runoff	539400 22.3	m2 mm				
A =	1,000V / (PnΔt)								
Af=	41766	m2							
Af provided =	42000	m2							
Vpit req'd =	30072	m3							
Vpit provided =	42000	m3	Af =	42000	m				
						d =	1	m	
NOTE: 10 SOAK-AWAY PITS WILL BE PROVIDED THAT TOTAL THE ABOVE VOLUME									

SPECIAL SERVICING REQUIREMENTS DUE TO ROCK AND GROUNDWATER

Groundwater levels in the monitoring wells on site ranged from 0.4 to 3.0 m below grade (Elev. 175.2 to 180.3 m).

In the event the base of the pond is to be constructed below the recorded, static groundwater table, dewatering will be required to allow the excavation of the pond and the construction of the clay liner. Due to this site being in a well head protected zone a liner would be required.

WETLAND ASESMENT

Refer to the EIS by Palmer for the evaluation of the wet land on site and the Wignell bog.

The lower reach (south of freedom trail, CNR tracks) of the Drain system has zero (or nearly zero) positive graded channel to the Lake (outlet). The lower lands are historically the Wignell Bog and are bog wetland that was formerly operated as a market garden and is now vacant land. The primary soil constituent of these lands is underlying peat, which acts as a sponge for runoff flows.

Recently it has been reported that there have been algae blooms within the Wignell bog. Algae blooms are primarily, a result of agricultural activity. Algae blooms lower dissolved oxygen concentrations in water, making it difficult for other plant and aquatic species to survive.

DISCUSSION/COMMENTARY AND OBSERVATIONS

The following are in no particular order:


- 1) The 1D/2D model approach is more realistic. The EWA model does not capture the culverts interacting with the channels in real time. The NPCA HEC-RAS has no respect to the attenuation effect behind the culverts.
- 2) The proposed infill development will not have a negative effect on the properties adjacent to the Site when developed.
- 3) Erosion is not a concern for the subject site. Refer to section on erosion review. Erosion control can be implemented as per MOE 2003 in the proposed wet ponds. Quantity control to detain and release the 25mm, 4-hour Chicago design storm over a 24-hour period
- 4) Snider Road will be raised in the post developed Elite site. It must be taken out of the flood plain.
- 5) Raising Snider Road creates a stacking effect on the flood waters on the east side. This can be seen in the HGL point 4. In the pre scenario the flood waters flow over Snider Road and in the post scenario they do not (compare Figure 23 to 31). This can be rectified in the final design by provided a ditch at point 4 to the new outlet culvert crossing on Snider Road.
- 6) There is a difference in the topography of the drain area through the developed area. This will create small differences in the sections (pre to post). Refer to 3D view of post-developed graded Site.

- 7) The aquatic, wetland and terrestrial resources as identified by Palmer and shown on the draft plan by Weston are to be protected.
- 8) All wet ponds will have bottom draw outlets to control temperature.
- 9) All pond outfall structures will be above the 100-year flood plain.
- 10) All ponds are outside the 100-year flood plain.

6.0 GRADING CONSIDERATION

Grading for the proposed site will be such that major overland flow will be directed to the proposed wet ponds. A conceptual grading design has been proposed on Figure S-8 in Appendix D showing how the site will tie into existing surrounding sites and direct overland runoff to the various wet ponds. Refer to Figure 43 for 3D view of the post developed graded site. The rendering is crude but shows that fill will be required.

Figure 42 – 3D view of post-developed graded Site



Note, the natural heritage sites are preserved
Note, the vertical scale is greatly exaggerated

7.0 RECOMMENDATIONS

We recommend the following:

1. A new central waste water pump station be located within the Elite development as shown in this report. A force main be routed from the pump station north to the future tunnel crossing the Welland canal. This crossing be co-ordinated with the Region of Niagara.
2. The pump station be sized to handle the entire Elite Development plus neighbouring properties that can economically drain to the new pump station.
3. The existing watermains be extended depending on the phasing plans and be looped (no long dead-end mains) as detailed in this report.
4. The NPCA flood shape file (regulatory) be implemented in the design of the subdivision.
5. That 6 SWMM ponds be incorporated into the design as detailed in this report.
6. That Snider Road be re-graded to take it out of the flood plain.
7. That a new culvert be established under neath Snider Road at the drain to allow a 100-year storm to pass.
8. That the NPCA regulatory flood model be updated once the geometry for Snider Road and the grading for the subdivision are established.
9. Infiltration galleries be implemented where the water table and rock elevation will be 1.0 m below the bottom of the gallery, in order to match water balance.
10. The aquatic, wetland and terrestrial resources as identified by Palmer and shown on the draft plan by Weston are to be protected.

8.0 CONCLUSIONS

The proposed development can be serviced with sanitary via extension of the existing sanitary sewer and upgrades as identified within. Water service can be provided via connecting to existing and extension through the subject property through looping as shown in this report. Stormwater management can be accomplished for quantity, quality, water balance, and infiltration as described in this report.

Based on the findings the site is serviceable and can be provided with adequate storm, sanitary and water services as described within the report.

9.0 REFERENCES

1. STORM WATER MANAGEMENT PLANNING AND DESIGN MANUAL, Ontario Ministry of the Environment, March 2003.
2. Engineering Guidelines for Servicing Land Under Development Applications December, 2012.
3. NIAGARA REGION WATER-WASTEWATER PROJECT DESIGN MANUAL, Revision 3, July 2023.
4. THE CITY OF WELLAND MUNICIPAL STANDARDS DESIGN CRITERIA, February 2013.
5. Niagara Peninsula Conservation Authority Stormwater Management Guidelines, March 10, 2017.
6. “Wignell Watershed Hydrology and Hydraulics Report”, EWA Engineers Inc., August 31, 2021.
7. “NIAGARA PENINSULA CONSERVATION AUTHORITY FLOOD PLAIN MAPPING WIGNELL DRAIN CITY OF PORT COLBORNE”, NIAGARA PENINSULA CONSERVATION AUTHORITY, August 2011.
8. “ENVIRONMENTAL IMPACT STUDY”, Elite Properties East of Port Colborne, Palmer, October 2023.
9. DESIGN GUIDELINES FOR DRINKING WATER SYSTEMS, by the Ministry of the Environment of Ontario (now The Ministry of the Environment, Conservation, and Parks; MECP), dated 2008.
10. Ministry of Environment “DESIGN GUIDELINES FOR SEWAGE WORKS 2008”
11. INFO-WORKS ICM 7.5 - Reference Manual, May 2016.
12. INFO-WATER PRO - Reference Manual, Latest edition.
13. NEW JERSEY STORM WATER BEST MANAGEMENT PRACTICES MANUAL, April 2004.
14. MNR Technical Guide – River and Streams Systems: Flooding Hazard Limits, 2002.
15. FEMA Chapter 4 - Flood Risk Assessment.
16. ROAD AND BRIDGE DECK DRAINAGE SYSTEMS by MTO, November 1982.
17. XPSWMM users Guide by INNOVYZE 2022.
18. EPA SWMM 5, Build 5.1.012, Manual.
19. LOW IMPACT DEVELOPMENT STORMWATER MANAGEMENT MANUAL, 2008, by Credit Valley Conservation Authority and Toronto Town Conservation Authority.

20. THE EROSION AND SEDIMENTATION CONTROL GUIDELINES FOR URBAN CONSTRUCTION prepared by the Greater Golden Horseshoe Area Conservation Authorities.

Respectfully Submitted;
The Odan Detech Group Inc.



April 18, 2024

John Krpan, M.S.C.E. P.Eng




Paul Hecimovic, P.Eng


APPENDIX A

Aerial Photo of Existing Site

Draft Plan of Proposed Development (reduced)

Aerial Photo of Existing Site





UNIT COUNT - PART 1		UNITS
SINGLE DETACHED 13.7m (45')	8	
SINGLE DETACHED 12.2m (40')	141	
SINGLE DETACHED 10.7m (35')	172	
SINGLE DETACHED 9.15m (30')	125	
LANE BASED TOWNHOUSE 8m (26')	139	
LANE BASED TOWNHOUSE 6.1m (20')	25	
STREET TOWNHOUSE 8m (26')	84	
STREET TOWNHOUSE 6.1m (20')	92	
CONDOMINIUM TOWNHOUSE 6.5m (21')	220	
TOTAL UNITS		1006
COMMERCIAL		2.50ha

UNIT COUNT - PART 5		UNITS
SINGLE DETACHED 13.7m (45')	0	
SINGLE DETACHED 12.2m (40')	54	
SINGLE DETACHED 10.7m (35')	0	
SINGLE DETACHED 9.15m (30')	0	
LANE BASED TOWNHOUSE 8m (26')	12	
LANE BASED TOWNHOUSE 6.1m (20')	0	
STREET TOWNHOUSE 8m (26')	0	
STREET TOWNHOUSE 6.1m (20')	0	
CONDOMINIUM TOWNHOUSE 6.5m (21')	48	
TOTAL UNITS		114
COMMERCIAL		2.43ha

UNIT COUNT - PART 2		UNITS
SINGLE DETACHED 13.7m (45')	17	
SINGLE DETACHED 12.2m (40')	128	
SINGLE DETACHED 10.7m (35')	217	
SINGLE DETACHED 9.15m (30')	78	
LANE BASED TOWNHOUSE 8m (26')	68	
LANE BASED TOWNHOUSE 6.1m (20')	73	
STREET TOWNHOUSE 8m (26')	34	
STREET TOWNHOUSE 6.1m (20')	32	
CONDOMINIUM TOWNHOUSE 6.5m (21')	204	
TOTAL UNITS		851
COMMERCIAL		2.43ha

UNIT COUNT - PART 3		UNITS
SINGLE DETACHED 13.7m (45')	0	
SINGLE DETACHED 12.2m (40')	9	
SINGLE DETACHED 10.7m (35')	12	
SINGLE DETACHED 9.15m (30')	5	
LANE BASED TOWNHOUSE 8m (26')	33	
LANE BASED TOWNHOUSE 6.1m (20')	0	
STREET TOWNHOUSE 8m (26')	0	
STREET TOWNHOUSE 6.1m (20')	0	
CONDOMINIUM TOWNHOUSE 6.5m (21')	44	
TOTAL UNITS		103
COMMERCIAL		2.43ha

UNIT COUNT - PART 4		UNITS
SINGLE DETACHED 13.7m (45')	9	
SINGLE DETACHED 12.2m (40')	16	
SINGLE DETACHED 10.7m (35')	36	
SINGLE DETACHED 9.15m (30')	0	
LANE BASED TOWNHOUSE 8m (26')	37	
LANE BASED TOWNHOUSE 6.1m (20')	33	
STREET TOWNHOUSE 8m (26')	0	
STREET TOWNHOUSE 6.1m (20')	37	
CONDOMINIUM TOWNHOUSE 6.5m (21')	0	
TOTAL UNITS		168
COMMERCIAL		2.43ha

LEGEND

- - - Study Area
- Commercial
- Parkland
- Significant Woodlands w/ 10m Buffer
- Non-PSW Wetlands w/ 30m Buffer
- Rare Vegetation Community
- 15m Municipal Drain Important/Marginal Fish Habitat Buffer
- Municipal Drain Important/Marginal Fish Habitat Buffer
- NPCA Floodplain
- SWM Pond

DEVELOPMENT STATISTICS:

Gross Study Area: 142.27ha
Estimated Net Developable Area: 99.68ha
(excluding SWM ponds & Regulated Areas)

Required Parkland: 1 ha per 300 units 7.30ha
Provided Parkland 4.69ha

Units per Net Hectare (2,242units/99.68ha) 22.49uph

SWM Pond: 8.90ha

UNIT COUNT	UNITS	%
SINGLE DETACHED 13.7m (45')	34	46%
SINGLE DETACHED 12.2m (40')	348	
SINGLE DETACHED 10.7m (35')	437	
SINGLE DETACHED 9.15m (30')	208	
LANE BASED TOWNHOUSE 8m (26')	289	19%
LANE BASED TOWNHOUSE 6.1m (20')	131	
STREET TOWNHOUSE 8m (26')	118	12%
STREET TOWNHOUSE 6.1m (20')	161	
CONDOMINIUM TOWNHOUSE 6.5m (21')	516	23%
TOTAL UNITS	2242	
COMMERCIAL	2.43ha	

Required Commercial GFA: 3,363m²

150m² per 100 unit

Commercial Land Area: 25,000m²

Estimated Commercial GFA (est. 25% coverage) 6,250m²



APPENDIX B

Figure S-1 - Proposed Global Sanitary Servicing (Schematic)

Figure S-2 - Conceptual Sanitary Servicing (Option 1)

Figure S-3 - Conceptual Sanitary Servicing (Option 2)

Figure S-4 - Sanitary Tributary Plan



LEGEND:

- PROPOSED SANITARY MANHOLE
- PROPOSED SANITARY SEWER
- ▨ EXISTING WASTEWATER TREATMENT PLANT (WWTP)
- SANITARY PUMP STATION (SPS)
- WOODLAND
- FLOOD PLAN (INCPN)
- PROPERTY LINE
- SANITARY TRIBUTARY AREA

DRAWING : **FIGURE S-1**
PROPOSED GLOBAL SANITARY SERVICING (SCHEMATIC)




CLIENT : **ELITE M.D. DEVELOPMENTS**
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT : **PROPOSED SUBDIVISION**
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

ODAN-DETECH
CONSULTING ENGINEERS

The Odan/Detech Group Inc. P: (905) 632-3811 F: (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2

DATE:	SCALE:	PROJECT No:
JAN 2024	1:5000	21247



- LEGEND:**
- PROPOSED SANITARY MANHOLE
 - PROPOSED SANITARY SEWER
 - SANITARY PUMP STATION
 - WOODLAND
 - FLOOD PLAN (NCPN)
 - PROPERTY LINE
 - SANITARY TRIBUTARY AREA

DRAWING : **FIGURE S-2**
CONCEPTUAL SANITARY SERVICING
(OPTION 1)




CLIENT : **ELITE M.D. DEVELOPMENTS**
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT : **PROPOSED SUBDIVISION**
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

ODAN-DETECH
CONSULTING ENGINEERS

The Odan/Detech Group Inc. P: (905) 632-3811 F: (905) 632-3363
5238 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2

DATE: JAN 2024	SCALE: 1:3000	PROJECT No: 21247
--------------------------	-------------------------	-----------------------------



SANTARY AND FLOOD PLAN

SCALE:
HOR. 1:150
VER. 1:300


LEGEND:

- PROPOSED SANITARY MANHOLE
- PROPOSED SANITARY SEWER
- SANITARY PUMP STATION
- WOODLAND
- FLOOD PLAN (NCPN)
- PROPERTY LINE
- SANITARY TRIBUTARY AREA

DRAWING : **FIGURE S-3**
CONCEPTUAL SAN SERVICING (OPTION 2)



CLIENT : **ELITE M.D. DEVELOPMENTS**
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT : **PROPOSED SUBDIVISION**
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

 **ODAN-DETECH**
CONSULTING ENGINEERS

The Odan/Detech Group Inc. P. (905) 632-3811 F. (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2

DATE: JAN 2024	SCALE: 1:3000	PROJECT No: 21247
--------------------------	-------------------------	-----------------------------



LEGEND:

- PROPOSED SANITARY MANHOLE
- ▶— PROPOSED SANITARY SEWER
- - - - - PROPERTY LINE
- - - - - SANITARY TRIBUTARY AREA

100' NET AREA (HA)
 (WITHOUT WOODLANDS AND PONDS)
 60' PEOPLE/Ha

DRAWING : **FIGURE S-4**
SANITARY TRIBUTARY PLAN

CLIENT : **ELITE M.D. DEVELOPMENTS**
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT : **PROPOSED SUBDIVISION**
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

ODAN-DETECH
CONSULTING ENGINEERS

The Odan/Detech Group Inc., P. (905) 632-3811 F. (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2



DATE: JAN 2024	SCALE: 1:5000	PROJECT No: 21247
--------------------------	-------------------------	-----------------------------

APPENDIX C

INFOWATER Pro (715023 - Port Colborne Water Model - MSP.aprx) existing and updated
Provided upon request.

APPENDIX D

Figure S-5 - Pre-Development Catchment Areas
Figure S-6 - Post-Development Catchment Areas (Local)
Figure S-7 - Conceptual Servicing Plan
Figure S-8 - Conceptual Grading Plan
Figure S-9 to S-16 - Conceptual Ponds Sections (Ponds A-F)



LEGEND:

- PROPERTY LINE
- TRIBUTARY CATCHMENTS AREA BOUNDARY
- EXISTING CONTOUR
- FLOOD PLAN (NCPN)
- TRIBUTARY AREA ID NO.
- TRIBUTARY AREA (HA)

FIGURE S-5
PRE-DEVELOPMENT CATCHMENT AREAS


CLIENT :
ELITE M.D. DEVELOPMENTS
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT :
PROPOSED SUBDIVISION
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

ODAN-DETECH
CONSULTING ENGINEERS

The Odan/Detech Group Inc. P: (905) 632-3811 F: (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2

DATE: JAN 2024	SCALE: 1:3000	PROJECT No: 21247
-------------------	------------------	----------------------



LEGEND:

- PROPERTY LINE
- TRIBUTARY CATCHMENTS AREA BOUNDARY
- WOODLAND
- PROPOSED POND
- FLOOD PLAN (INCPN)
- TRIBUTARY AREA ID NO. TO POND
- TRIBUTARY AREA (HA)
- PROPOSED MAJOR STORM OVERLAND FLOW

DRAWING : **FIGURE S-6**
POST-DEVELOPMENT CATCHMENT AREAS (LOCAL)


CLIENT : **ELITE M.D. DEVELOPMENTS**
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO


PROJECT : **PROPOSED SUBDIVISION**
KILLALY STREET EAST
PORT COLBORNE, ONTARIO



ODAN·DETECH
CONSULTING ENGINEERS
The Odan/Detech Group Inc. P: (905) 632-3811 F: (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2

DATE: JAN 2024	SCALE: 1:3000	PROJECT No: 21247
-------------------	------------------	----------------------





MAIN STREET EAST (HWY 3)

ELIZABETH STREET

LORRAINE STREET

KILLALY STREET EAST

SAINT THERÈSE
CATHOLIC
ELEMENTARY
SCHOOL

SWIDER ROAD (UNDEVELOPED)

LEGEND:

- PROPOSED STORM MANHOLE
- PROPOSED STORM SEWER
- PROPERTY LINE
- WOODLAND
- PROPOSED POND
- FLOOD PLAN (INCPN)



FIGURE S-7
CONCEPTUAL STORM SERVING PLAN

ELITE M.D. DEVELOPMENTS
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROPOSED SUBDIVISION
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

ODAN·DETECH
CONSULTING ENGINEERS
The Odan/Detech Group Inc. P: (905) 632-3811 F: (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2

DATE: JAN 2024 SCALE: 1:3000 PROJECT No: 21247




LEGEND:

- × 100.00 EXISTING SPOT ELEVATION
- × (100.00) PROPOSED ELEVATION
- × [100.00] FUTURE ELEVATION
- 195.50 EXISTING CONTOUR
- ➔ PROPOSED EMERGENCY OVERLAND FLOW
- Non-PSW Wetland w/30m BUFFER
- Significant Woodland w/10m BUFFER
- PROPOSED POND
- FLOOD PLAN (NCPN)
- PROPERTY LINE




DRAWING : **FIGURE S-8**
CONCEPTUAL GRADING

CLIENT : **ELITE M.D. DEVELOPMENTS**
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT : **PROPOSED SUBDIVISION**
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

 **ODAN+DETECH**
CONSULTING ENGINEERS
The Odan+Detech Group Inc. P: (905) 632-3811 F: (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2

DATE: **JAN 2024** SCALE: **1:3000** PROJECT No: **21247**



LEGEND:

- ⊙ PROPOSED STORM MANHOLE
- PROPOSED STORM SEWER
- × 100.00 EXISTING SPOT ELEVATION
- × (100.00) PROPOSED ELEVATION
- × (100.00)CL PROPOSED CENTERLINE OF ROAD ELEVATION
- PROPOSED SLOPE (3:1 OR HIGHER)
- PROPERTY LINE
- NWL NORMAL WATER LEVEL



DRAWING : **FIGURE S-9**
CONCEPTUAL POND A SECTION AND GRADING

CLIENT : **ELITE M.D. DEVELOPMENTS**
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT : **PROPOSED SUBDIVISION**
KILLALY STREET EAST
PORT COLBORNE, ONTARIO



ODAN-DETECH
CONSULTING ENGINEERS
The Odan/Detech Group Inc. P: (905) 632-3811 F: (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 8K2

DATE: **JAN. 2024** SCALE: **H-1000 V-200** PROJECT No: **21247**



LEGEND:

- PROPOSED STORM MANHOLE
- PROPOSED STORM SEWER
- EXISTING SPOT ELEVATION
- PROPOSED ELEVATION
- PROPOSED CENTERLINE OF ROAD
- ELEVATION
- WOODLAND
- FLOOD PLAN (NCPN)
- PROPOSED SLOPE (3:1 OR HIGHER)
- PROPERTY LINE
- NWL NORMAL WATER LEVEL



H-1000
V-200

DRAWING : **FIGURE S-10
CONCEPTUAL POND B
SECTION AND GRADING**



CLIENT : **ELITE M.D. DEVELOPMENTS**
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT : **PROPOSED SUBDIVISION**
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

ODAN-DETECH
CONSULTING ENGINEERS

The Odan-Detech Group Inc. P: (905) 632-3811 F: (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 9K2

DATE: **JAN. 2024** SCALE: **PROJECT No. 21247**




LEGEND:

- ⊙ PROPOSED STORM MANHOLE
- ➔ PROPOSED STORM SEWER
- × 100.00 EXISTING SPOT ELEVATION
- × (100.00) PROPOSED ELEVATION
- × (100.00)CL PROPOSED CENTERLINE OF ROAD ELEVATION
- WOODLAND
- PROPOSED SLOPE (3:1 OR HIGHER)
- - - - - PROPERTY LINE
- NWL NORMAL WATER LEVEL


DRAWING : **FIGURE S-12**
CONCEPTUAL POND D
SECTION AND GRADING



CLIENT : **ELITE M.D. DEVELOPMENTS**
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT : **PROPOSED SUBDIVISION**
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

**ODAN-DETECH**
CONSULTING ENGINEERS
The Odan/Detech Group Inc. P: (905) 632-3811 F: (905) 632-3383
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2

DATE: JAN. 2024	SCALE: H-1250 V-250	PROJECT No: 21247
--------------------	---------------------------	----------------------





POND D to EXISTING CREEK- SECTION E

LEGEND:

- PROPOSED STORM MANHOLE
- PROPOSED STORM SEWER
- x 100.00 EXISTING SPOT ELEVATION
- x (100.00) PROPOSED ELEVATION
- x (100.00)CL PROPOSED CENTERLINE OF ROAD ELEVATION
- FLOOD PLAN (NCPN)
- - - - - PROPERTY LINE

DRAWING : **FIGURE S-13**
CONCEPTUAL STORM SECTIONS
POND D TO EXISTING CREEK



CLIENT :
ELITE M.D. DEVELOPMENTS
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT :
PROPOSED SUBDIVISION
KILLALY STREET EAST
PORT COLBORNE, ONTARIO

ODAN-DETECH
CONSULTING ENGINEERS
The Odan/Detech Group Inc. P: (905) 632-3811 F: (905) 632-3363
5230 SOUTH SERVICE ROAD, BURLINGTON, ONTARIO, L7L 5K2

DATE: JAN. 2024	SCALE:	PROJECT No: 21247
---------------------------	--------	-----------------------------

H-1500
V-300



LEGEND:

- ⊙ PROPOSED STORM MANHOLE
- ➔ PROPOSED STORM SEWER
- x 100.00 EXISTING SPOT ELEVATION
- x (100.00) PROPOSED ELEVATION
- x (100.00)CL PROPOSED CENTERLINE OF ROAD ELEVATION
- FLOOD PLAN (NCPN)
- PROPOSED SLOPE (3:1 OR HIGHER)
- PROPERTY LINE
- NWL NORMAL WATER LEVEL


DRAWING : FIGURE S-14 CONCEPTUAL POND E SECTION AND GRADING

CLIENT :
ELITE M.D. DEVELOPMENTS
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO






PROJECT :
PROPOSED SUBDIVISION
KILLALY STREET EAST
PORT COLBORNE, ONTARIO



DATE: JAN. 2024 SCALE: H-1250 V-250 PROJECT No: 21247





-  **PROPOSED STORM MANHOLE**
 **PROPOSED STORM SEWER**
 x 100.00' **EXISTING SPOT ELEVATION**
 x (100.00)' **PROPOSED ELEVATION**
 x (100.00)' CL **PROPOSED CENTERLINE OF ROAD**
ELEVATION
 **FLOOD PLAN (NCPN)**
 **PROPOSED SLOPE (3:1 OR HIGHER)**
 **PROPERTY LINE**
NWL **NORMAL WATER LEVEL**

DRAWING : FIGURE S-16
CONCEPTUAL POND F
SECTION AND GRADING

CLIENT :
ELITE M.D. DEVELOPMENTS
102-3410 SOUTH SERVICE ROAD
BURLINGTON, ONTARIO

PROJECT :
**PROPOSED SUBDIVISION
KILLALY STREET EAST
PORT COLBORNE, ONTARIO**



DATE: JAN. 2024

SCALE:
H-1250
V-250

PROJECT No:
21247