



## **Terra-Dynamics Consulting Inc.**

**432 Niagara Street, Unit 2 St. Catharines, ON L2M 4W3**

June 3, 2022

2600261 Ontario Inc.  
c/o Alex Troop  
Alliance Homes Ltd.  
6048 Highway #9  
Schomberg, ON L0G 1T0

Re: Water Balance Study, Northland Estates, Westside Road Con. 2 PT Lot 31, Port Colborne, ON

Dear Mr. Troop,

### **1.0 Introduction and Background Information**

Terra-Dynamics Consulting Inc. (Terra-Dynamics) respectfully submits this water balance study of 2600261 Ontario Inc.'s Northland Estates development, located in Port Colborne, Ontario (Site) (Figure 1). Proposed development of the 15.9 hectares includes townhouses, single residential and apartments as well as stormwater management and park/open space (Upper Canada Consultants, 2022, Appendix B). The Site is located south of Barrick Road and west of Highway 58/West Side Road, and is legally described as Lot 31, Concession 2, Humberstone Township.

The Niagara Peninsula Conservation Authority (NPCA) requires a water balance as part of an updated Environmental Impact Study for the Site (City of Port Colborne, 2021). The purpose of the water balance assessment is to inform site design whereby there is *"no negative impact to the hydrologic function of the wetland"* (NPCA, 2021). The wetland being referred to in this case is the Locally Significant Onondaga Escarpment Wetland Complex (MNRF, 2009).

This water balance assessment includes:

1. An assessment of the water balance of the adjacent wetland, specifically analyzing the role of the Site in supplying the wetland with water; and
2. An overview of potential impacts, discussion of potential alternatives and proposed mitigation measures.

This water balance exceeds the requirements for "low risk" evaluation as specified by the TRCA (2017) and was also completed to generally conform to the Conservation Authority Guidelines for Development Applications (Conservation Ontario, 2013).

### **2.0 Methodology**

Primary tasks completed as part of the water balance study included:

- A. Characterization of the physical setting using published information from the following government agencies: (i) the Ontario Ministry of Agriculture, Food and Rural Affairs (OMAFRA), (ii) the Ministry of the

Environment, Conservation and Parks (MECP), (iii) the Niagara Peninsula Conservation Authority (NPCA), and (iv) the Ontario Geological Survey (OGS). Existing on-site investigation reports (e.g. Shaheen & Peaker Limited, 2002, GEMS Inc., 2020 and Beacon Environmental, 2022) were also reviewed.

- B. A site visit was completed in the spring of 2022, which included hand-auger soil sampling and subsequent laboratory grain-size analyses, and observations of on-site surface water conditions;
- C. Modelling of pre-development and post-development monthly water balance conditions through consideration of: surface water catchments, land cover, soils, climate normals and wetland hydroperiods in order to determine if the site design is sufficient; and
- D. A Wetland Risk Evaluation (TRCA, 2017).

### 3.0 Physical Setting

The Site is primarily located on the Onondaga Escarpment with the Haldimand Clay Plain to the south/south-west (Chapman and Putnam, 1984). The Onondaga Escarpment is defined as:

*“a north-facing, east-west trending bedrock cuesta with approximately 10 metres of relief. A cuesta is a hill or ridge with a gentle slope on one side and a steep slope on the other. The Onondaga Escarpment (limestone plain) forms the northern drainage boundary for a number of catchments... Eagle Marsh drain....”* (AquaResource Inc. and NPCA, 2009).

The Site is located on the gentle southern slope of the Onondaga Escarpment, as shown on Figure 3 underlain by loam and clay loam Farmington and Franktown soils (Kingston and Presant, 1989).

The Site is undeveloped but was historically farmed and *“successional thicket-type vegetation comprises a large area of the site to the east while the west side of the Site transitions into wetland and a large woodland area”* (GEMS, 2020).

#### 3.1 Topography

The ground surface elevation varies from 181 to 185 metres above sea level (m ASL) with the ground surface sloping to the south-southwest (Figure 2). The Site is fairly flat with 2% slope in the upper northeast corner but less than 1% slope in the southwest portion of the Site with the wetlands.

The Onondaga Escarpment Locally Significant Wetland (LSW) (Section 3.7, MNRF, 2009) is located within approximately the 181.1 m ASL contour based upon ground surface contours generated from NPCA's 2018 digital terrain model (Figure 2).

#### 3.2 Surface Water

The Site is located within the upper reaches of the Eagle Marsh Drain Catchment EMD\_W200 of the Lake Erie North Shore Watershed Planning Area (Figure 1) (AquaResource Inc. and NPCA, 2009). The actual Eagle Marsh Drain begins approximately 500 m to the south of the southwest corner of the Site (Figure 1), and is classified as Type F, intermittent flow (OMAFRA, 2022). NPCA (2017) has mapped a

single waterbody at the Site (Figure 2) and identified it as an intermittent/ephemeral swamp slough. NPCA has defined slough forests as “*forested areas with undulating land that contain seasonally ponded areas... and ridges of higher land*” (NPCA, 2010). During our site visit on March 16, 2022, we observed a series of small slough ponds within this area on-site.

A former east-west watercourse is noted within the Site along the southern boundary, but was observed as heavily overgrown and not maintained for flow.

### 3.2.1 Surface Water Catchments

A digital terrain model from NPCA (2018) was processed in a Geographic Information System (GIS) to determine the surface water catchments for the area mapped within the 2019 wetland boundary (Section 3.7, Figure 5), these are a combination of two Ecological Land Classification (ELC) communities (Beacon, 2022). These two ELC communities are summarized as follows:

1. Oak Mineral Deciduous Swamp (SWD-1), is 2.81 hectares with three modelled drainage areas:
  - (i) Drainage Area A – 0.37 hectares or 13%, modelled as having an upgradient drainage area of 1.74 hectares;
  - (ii) Drainage Area B – most of the swamp (2.40 hectares, or 85%) is modelled as having a very limited upgradient drainage area of 0.30 hectares, mostly within the 30 m buffer; and
  - (iii) Drainage Area C – a very small portion (0.04 hectares, or less than 2%), modelled not to receive external runoff.
2. Mineral Thicket Swamp (SWT-2) is 2.45 hectares with three modelled drainage areas:
  - (i) Drainage Area A' – 1.13 hectares or 46%, modelled as having an upgradient drainage area that is within the SWD-1;
  - (ii) Drainage Area B' – 1.13 hectares or 46%, modelled as limited to within the feature; and
  - (iii) Drainage Area C' – 0.18 hectares or 7%, modelled to runoff to the east.

### 3.3 Soils

Most of the Site's soils (>80%) have been regionally mapped as less than 100 cm thick ('*shallow phase*') imperfectly drained loam/clay loam Franktown soils, with the northeast corner of the Site mapped as less than 50 cm thick ('*very shallow phase*') well drained loam Farmington soils (Kingston and Presant, 1989, Appendix A – Figure A-1). These reported shallow soil conditions (Figure 3) were confirmed by a previous geotechnical study (Figure 2 - Shaheen & Peaker Limited, 2002) and hand-auger holes completed during our site visit (Figure 2).

The majority of the Site (>80%) is reported as hydrological soil groups (HSGs) 50% B / 50% C (Appendix A – Figure A-1, Table 1). However, based upon wetland soil sampling at the Site and laboratory grain-size analyses, HSGs 50% C/50% D are proposed as representative of the silty clay soils in the wetland area (Section 3.7). This is explained herein:

1. Two soil samples collected by hand-auger were selected for submission for grain-size analyses (Figure 2, SS2 and SS3, Appendix A) and both are classified as *poorly sorted clay with fines* (Appendix A). Soil samples SS1 and SS4 were of similar grain-size consistency.
2. The hydraulic conductivity (i.e. permeability) was calculated as  $<10^{-8}$  m/s for both samples using the Excel-tool HydroGeoSieveXL (Devlin, 2015). The hydraulic conductivities are reasonable for silty clay to clay till compared to published values for the province of Ontario (MECP, 2006).
3. The low hydraulic conductivity/ permeability (MECP, 2008) results in low infiltration and ponding of surface water on the ground surface.

Farmington soils in the northeast corner are regionally mapped as HSG B.




Figure 3 - Schematic landscape cross-section showing the relationship of soils to bedrock in the vicinity of the Wainfleet Bog (Kingston and Present, 1989)

Table 1 - Hydrologic Soil Groups (USDA, 1986)

HSG Group	Soil description	Infiltration Rates (mm/hour)
A	sand, loamy sand or sandy loam	>7.6
B	silt loam or loam	7.6-3.8
C	sandy clay loam	3.8-1.3
D	clay loam, silty clay loam, sandy clay, silty clay or clay	<1.3

### 3.4 Surficial Geology

A third of the Site is mapped as low permeability clay and silt in the southwest corner by the Ontario Geological Survey (OGS) (Feenstra, 1984). This area generally corresponds with the wetlands mapped at the Site (Figure 2, Beacon Environmental, 2022 and Section 3.7). Consequently, the low permeability clay and silt are interpreted to perch the water necessary for the wetlands. Hand-auger soil sampling completed in this area (SS1, SS2, SS3 and SS4, Figure 2) confirmed silty clay overlying silty clay diamicton. Diamicton is “a non-sorted or poorly sorted ...sediment containing a wide range of particle sizes derived from a broad provenance... and may have a fine-grained matrix” (Menzies, 2009).



Bedrock was inferred by hand-auger refusal at between 0.8 and 1.0 metres at locations SS1, SS3 and SS4 (Figure 2). Bedrock was inferred by hand-auger refusal at 0.5 m at SS2.

The remaining two thirds of the Site is mapped as bedrock at surface, based on the OGS criterion being less than 1 m of overburden above the bedrock surface (Figure 2). A geotechnical test pit investigation of the Site confirmed topsoil over bedrock as being very thin ranging from 0.2 to 0.6 m at the nine locations completed, which were generally outside the wetland area due to the thick vegetation at the wetland area (Figure 2, Shaheen and Peaker, 2002).

### 3.5 Bedrock

The Site is primarily underlain by the Bois Blanc Formation bedrock consisting of *“light grey to greenish grey, variably argillaceous, locally sandy, fine-grained, very cherty limestone (or minor dolostone) (Figures 3 and 4). Chert commonly occurs as thick white to light bluish white nodules and lenses that locally constitute over 75% of the rock mass...It tends to weather rubbly because of its argillaceous nature and high chert content.”* (Armstrong, 2017). The southwest corner is reported as the Edgecliff Member of the Onondaga Formation, which overlies the Bois Blanc and is cherty, fossiliferous, locally argillaceous limestone.

### 3.6 Hydrogeologic Setting

A hydrogeologic cross-section through the Site was prepared (Figure 4) using Ministry of the Environment, Conservation and Parks (MECP) water well and monitoring well records (MECP, 2022, Appendix A), as well as on-site data. Details of this section include:

1. Local water wells (Figure 2) access the underlying shallow bedrock aquifer. Groundwater table levels were reported as between 3.0 and 4.5 metres below ground surface (m BGS);
2. Wetland water levels are perched above the unsaturated bedrock by low permeability silty clay (Section 3.3); and
3. The vertical gradient from wetland water levels to the bedrock aquifer is downwards.

### 3.7 Wetlands

Approximately 1 hectare of the Locally Significant Onondaga Escarpment Wetland Complex (MNRF, 2009) extends onto the western portion of the Site (Figure 2). The Ministry of Natural Resources and Forestry (MNRF, 2009) have mapped this as an isolated swamp wetland with deciduous trees as the dominant vegetation (Figure 2). This polygon is within an area classified as Ecological Land Classification SWD-1, Oak Mineral Deciduous Swamp, by Beacon Environmental (2022) (Figure 2).

An area of SWT-2 Mineral Thicket Swamp is mapped to the south (Beacon Environmental, 2022).

A wetland boundary was previously staked and surveyed in 2019 by GEMS, NPCA and Niagara Region staff (Figure 2) along the eastern boundary of these features.

### 3.7.1 Wetland Characterization

The swamps are classified as a *surface water depression wetlands* (Figure 6). A surface water depression wetland is summarized as:

*“wetland ... dominated by surface runoff and precipitation, with little groundwater outflow due to a layer or low-permeability soils...”* (Mitsch and Gosselink, 2007). Low permeability soils were noted on-site (Section 3.3).




Figure 6 - Surface water depression wetland (Mitsch and Gosselink, 2007)

### 3.7.2 Wetland Hydroperiod

A hydroperiod is defined as *“the seasonal pattern of the water level of a wetland...It characterizes each type of wetland, and the constancy of its pattern from year to year ensures a reasonable stability for that wetland. It defines the rise and fall of a wetland’s surface and subsurface water by integrating all of the inflows and outflows”* (Mitsch and Gosselink, 2007).

The province has identified that the Locally Significant Onondaga Escarpment Wetland Complex is seasonally flooded for a period of ‘2 weeks to a month’ (MNRF, 2009). This appears less than a published Canadian swamp hydroperiod (Figure 7); the shaded lower portion of the hydroperiod graph corresponds with below ground surface and the months of the year listed along the x-axis. Mitsch and Gosselink (2007) report that the *“hydroperiods of many bottomland hardwood forests and swamps have distinct periods of surface flooding in the winter and early spring due to snow and ice conditions followed by spring floods but otherwise have a water table that can be a meter or more below the surface”*.




Figure 7 – Canadian Swamp Hydroperiod (Mitsch and Gosselink, 2007)

### 3.7.3 Soil Water Holding Capacity

The SWD-1 soil water holding capacity (SWHC) was calculated as 375 mm based upon the soils identified on-site (Section 3.3) and previous swamp SWHC designations used by NPCA in their water budgeting study (AquaResource Inc. and NPCA, 2009).

### 3.8 Pre-development Subwatershed Water Balance Modelling

NPCA previously completed water balance modelling for 1991-2005, as part of provincial water budgeting for the source water protection program (AquaResource Inc. and NPCA, 2009). This modelling was completed at 1-hour time steps with a filled-in meteorological dataset including solar radiation for calculation of evapotranspiration. Modelled annual and monthly water balance results were obtained for the Lake Erie North Shore Eagle Marsh Drain W200 (LENS\_EMD\_W200) Catchment (Tables 2 and 3, respectively) (AquaResource Inc. and NPCA, 2009).

**Table 2 - Water Balance 15-year (1991-2005) Averages**

Catchment	Precipitation	Actual Evapotranspiration	Annual Surplus	Infiltration*	Recharge	Runoff
	(mm/year)					
LENS_EMD_W200	968	450	518	170	85	348

Notes: \* - Infiltration is interflow plus recharge

**Table 3 - Monthly Runoff and Infiltration (Catchment LENS\_EMD\_W200)**

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Runoff (mm)	33.7	31.0	50.6	47.6	32.5	16.0	6.8	5.8	16.8	24.4	51.6	31.6
Infiltration (mm)	13.3	12.4	17.6	10.5	4.0	1.3	0.2	0.1	0.4	2.4	9.7	13.3

### 4.0 Water Balance Assessment

A monthly water balance assessment has been completed for the Oak Mineral Deciduous Swamp (SWD-1) (Figure 2), as informed by the Conservation Authority Guidelines for Development Applications (Conservation Ontario, 2013) and TRCA's guidance for water balances (2012). As the Mineral Thicket Swamp (SWT-2) is (i) downgradient of the SWD-1, and (ii) self-contained with respect to drainage

(Section 3.2.1) preservation of the SWD-1 ensures any surface water supply under pre-development conditions should continue.

It is noted that the Ministry of the Environment, Conservation and Parks (2003) water balance approach is typically concerned with the evaluation of post-development to prevent (i) increased runoff, and/or (ii) reduction in groundwater recharge. However, given the wetland characterization (Section 3.7.1) any contribution to hydrologic function with respect to the wetlands is via additional surface water flow, not groundwater discharge. Consequently, maintenance of pre-development monthly saturated conditions via runoff to maintain the wetland hydroperiod is the criteria for the water balance assessment.

#### 4.1 Monthly Water Balance Example

An example of water balance modelling from the University of Waterloo is shown below (Figure 8). Annual groundwater recharge begins in the fall following 'soil water utilization' and 'deficit' in the summer. Soil water utilization corresponds with evapotranspiration exceeding the precipitation supply. Annual groundwater recharge occurs during the same time period that groundwater levels rise. However, in this example it is noted that the soil water holding capacity (SWHC) modelled was only 100 mm compared to the higher SWHC of the downgradient SWD-1 of 375 mm.




Figure 8 – Brantford Average Water Balance (Sanderson, 2004)

#### 4.2 Wetland Water Balance

A monthly water balance for the SWD-1 swamp was completed using the U.S. Geological Survey (USGS) Monthly Water Balance Model (McCabe and Markstrom, 2007), which considers direct precipitation while runoff to the wetland is added using the NPCA monthly modelled results for the catchment. For

temperature and precipitation, climate normal inputs (1981-2010) from Port Colborne Station ID 6136606 were used (Environment Canada, 2022). The monthly water balance modelling results of the SWD-1 swamp are summarized below and in Table 4:

1. Potential evapotranspiration exceeded precipitation for June, July and August, i.e. soil water utilization occurred;
2. SWD-1 swamp soil water holding capacities were less than saturated, i.e. less than 375 mm, for the summer months (June through September), as well as October; and
3. Soil water recharge occurred in September and October.

**Table 4 – Monthly Wetland Water Balance (mm)**

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Precipitation (mm)</b>	73	57	67	76	90	79	82	83	98	90	101	89
<b>Potential (mm) Evapotranspiration</b>	10	12	21	40	71	105	127	105	63	34	18	11
<b>Soil Moisture (mm)</b>	375	375	375	375	375	<b>345</b>	<b>300</b>	<b>279</b>	<b>308</b>	<b>360</b>	375	375
<b>Soil Water<sup>1</sup> Depletion (mm)</b>						30	75	96	67	15		

Notes: <sup>1</sup> Difference between the SWHC (375 mm) and the modelled soil moisture

#### 4.3 Wetland Water Balance Assessment

As introduced in Section 4.0, “*maintenance of pre-development monthly saturated conditions via runoff to maintain the wetland hydroperiod is the criteria for the water balance assessment*”. Under pre-development conditions, two drainage areas are modelled to provide upgradient runoff to SWD-1 (Section 3.2.1): (i) Upgradient area A, 1.74 ha and (ii) Upgradient area B 0.30 ha (Figure 5). These upgradient areas are described as follows:

- A. Upgradient area A is modelled to maintain pre-development saturated soil conditions in Drainage Area A of SWD-1 in the summer months of June, September and October (Table 5 – Bolded) but not July and August (i.e. the upgradient area required to maintain pre-development saturated soil conditions during July and August is greater than the 1.74 ha). The proposed 30 m buffer (0.3 ha), and the additional upgradient Environmental Protection Area (EPA) of 0.5 ha is sufficient to maintain saturated conditions for June and October being 0.8 ha (Table 5, Figure 5). The incorporation of rear lot drainage (0.2 ha), and regrading of drainage of the northeast corner of the EPA towards the wetland (0.26 ha) as well as continued off-site runoff (0.04 ha), will provide over 85% of pre-development conditions in September. This is a reasonable effort to maintain pre-development runoff given the variability in September precipitation, e.g. 1981-2010 average 98 mm, 2021 September 153 mm, 2020 61 mm, and 2019 110 mm.
- B. Upgradient area B is modelled to be insufficient under pre-development conditions to maintain saturation downgradient in Drainage Area B of SWD-1 in the summer months (i.e. the upgradient area required to maintain pre-development saturated soil conditions is greater than the 0.30 ha) (Table 5). Therefore, maintenance of the hydroperiod in this downgradient area is primarily dependent upon direct precipitation not upgradient surface water supply via runoff. This would be

similar to the expected below ground surface water level for a SWD-1 swamp summer hydroperiod (Figure 7, Section 3.7.2). Consequently, the proposed 30 m buffer is hydrologically sufficient for this portion of the SWD-1 swamp.

**Table 5 – Modelled Summer Runoff to SWD-1 Swamp**

Month	Jun	Jul	Aug	Sep	Oct
<b>Soil Water<sup>1</sup> Depletion (mm)</b>	30	75	96	67	15
<b>SWD-1 Drainage area A Soil Water Depletion<sup>2</sup> (m<sup>3</sup>)</b>	111	278	355	248	56
<b>SWD-1 Drainage area B Soil Water Depletion<sup>2</sup> (m<sup>3</sup>)</b>	720	1,800	2,304	1,608	360
<b>Modelled Runoff (Section 3.8) (mm)</b>	16	7	6	17	24
<b>Upgradient area<sup>3</sup> required to produce saturated wetland – Drainage Area A (ha)</b>	<b>0.7</b>	4.0	5.9	<b>1.5</b>	<b>0.2</b>
<b>Upgradient area<sup>3</sup> required to produce saturated wetland – Drainage Area B (ha)</b>	4.5	25.7	38.4	9.5	1.5

Notes: <sup>1</sup> Difference between the SWHC (375 mm) and the modelled soil moisture

<sup>2</sup> Depletion depth multiplied by the downgradient area of SWD-1 swamp (Section 3.7, Figure 5).

<sup>3</sup> Volume of soil water depletion (m<sup>3</sup>) divided by monthly modelled runoff (mm) (from Table 3) converted to hectares

As the Mineral Thicket Swamp (SWT-2) is (i) downgradient of the SWD-1, and (ii) self-contained with respect to drainage (Section 3.2.1) preservation of the SWD-1 ensures any surface water supply under pre-development conditions should continue.

#### 4.4 Wetland Risk Evaluation

##### 4.4.1 Magnitude of Hydrological Change

TRCA's wetland risk evaluation (2017) decision tree (Figure 9) includes four key hydrological change criteria:

- 1) Impervious cover in catchment;
- 2) Change in catchment size;
- 3) Dewatering; and
- 4) Impact to recharge areas.

(1) The amount of impervious cover in the SWD-1 upgradient catchments are inconsequential as the on-site wetland catchment drainage areas are planned to be changed (Upper Canada Consultants Engineers/Planners, 2022, Appendix B).

(2) The surface water catchments upgradient of the SWD-1 swamp will be reduced upon development of the Site, as Drainage Area A and Drainage Area B are calculated to be reduced by (a) 25%, and (b) less than 10%, respectively.

(3) Construction dewatering should not affect the swamp as it is perched above the bedrock aquifer. Construction dewatering may not even be required due to the expected depth of the water table in the bedrock (Figure 4).

(4) No impacts to SWD-1 swamp recharge areas are predicted as TRCA (2017) defines this as *“replacement of existing soils with significantly less permeable materials”* and the on-site soils are already of low permeability. In addition, there are no locally significant recharge areas to be impacted as these are defined by TRCA (2017) as *“highly porous sedimentary deposits or otherwise having high hydraulic conductivity”*.

*“The highest magnitude category with one or more criteria satisfied determines the potential magnitude of change”* with the magnitude thresholds of less than 10% change as low, 10-25% medium and greater than 25% high (TRCA, 2017). Therefore, a high hydrologic risk is assigned based upon the magnitude of change in upgradient catchment area for downgradient Drainage Area A (13% of the SWD-1), but only low for the downgradient Drainage Area B (85% of the SWD-1) (Figure 5). However, as discussed in Section 4.3, hydrologic impacts to the downgradient SWD-1 swamp are not predicted.


#### **4.4.2 Sensitivity of the Wetlands**

The risk assignment (Figure 9) is also to consider the type of wetland, and their hydrological sensitivity (TRCA, 2017). The SWD-1 Oak Mineral Deciduous swamp has a medium hydrological sensitivity (TRCA, 2017).

#### **4.4.3 Risk Assignment**

As per Figure 9, a medium risk is assigned based upon a (i) high magnitude of hydrological change for Drainage Area A and (ii) a medium wetland sensitivity. The TRCA recommended study, modelling and mitigation requirements are:

- (i) Pre-development monitoring as outlined in the Wetland Water Balance Monitoring Protocol (TRCA, 2016).
  - However, this is not recommended, or required, as sufficient runoff is modelled to sustain the wetland post-development, and modelled hydrologic conditions reasonably match those reported by the province (MNRF, 2009).
- (ii) Continuous hydrological modelling at daily aggregated to weekly resolution.
  - Existing modelling (completed at 1-hour time steps) completed by NPCA was utilized for this report (AquaResource Inc. and NPCA, 2009) as part of a monthly analysis. This existing work could be re-visited to extract weekly results, however this would appear to have no benefit.
- (iii) Design of a mitigation plan to maintain the wetland water balance, in some cases an interim mitigation plan may also be required.
  - Mitigation includes rear yard runoff of lots adjacent the EPA, and grading of the northeast corner of the EPA to the wetland, providing mitigation for maintenance of the wetland hydroperiod where required.



**Figure 9 - Wetland Risk Evaluation Decision Tree (TRCA, 2017)**

## 5.0 Conclusions and Recommendations

The following conclusions are provided:

1. The Site is 15.9 hectares, with 1 hectare of locally significant wetland on-site, as well as an additional 4.3 hectares of wetland as designated by NPCA.
2. The Site is primarily on the Onondaga Escarpment with the Haldimand Clay Plain in the downgradient southwest portion of the Site.
3. The swamp is perched on low permeability silty clay in the downgradient southwest portion of the Site.
4. The swamp has an expected hydroperiod of *“distinct periods of surface flooding in the winter and early spring due to snow and ice conditions followed by spring floods but otherwise have a water table that can be a meter or more below the surface”*.
5. A monthly water balance for the downgradient swamp (before considering runoff to the wetland) identified potential evapotranspiration as exceeding precipitation for June, July, August, September and October, with soil water holding capacities less than saturated.



6. Monthly runoff modelling completed by NPCA reported runoff amounts for June, July, August, September and October of 16, 7, 6, 17 and 24 mm/month, respectively.
7. Pre-development water balance modelling for the downgradient SWD-1 swamp indicates upgradient lands for the:
  - a. Northern portion (Drainage Area A) would be sufficient to maintain saturated conditions during June, September and October but not July and August.
  - b. Majority (85%) of the SWD-1 (i.e. Drainage Area B) would be insufficient to maintain saturated conditions during June to October.
8. The TRCA wetland risk assigned is calculated as medium, for the northern portion of the swamp (13%) (Drainage Area A) based upon the potential for a high magnitude of hydrological change and medium wetland sensitivity, and low for the majority (87%) of the swamp (i.e. Drainage Area B).
9. Residential development of the Site should not negatively impact the hydrology of the adjacent SWD-1 swamp. This is because precipitation is the primary source of surface water supply during the summer period and for the northern portion rear yard runoff and grading should provide sufficient additional runoff during September.
10. Residential development of the Site should not negatively impact the hydrology of the SWT-2 swamp as it is downgradient of the SWD-1, and self-contained with respect to drainage.


The following recommendations are provided:

1. Implement rear yard lot drainage towards the wetland/EPA for adjacent lots; and
2. Grade surface water drainage in the northwest corner of the Environmental Protection Area towards the SWD-1 wetland.


We trust this information is sufficient for your present needs. Please do not hesitate to contact us if you have any questions.

Yours truly,

TERRA-DYNAMICS CONSULTING INC.



Jayme D. Campbell, P. Eng.  
Senior Water Resources Engineer




Annie Michaud, M.Eng., P. Eng.  
Senior Water Resources Engineer

cc. Matt Kernahan, MCIP, RPP  
Ron Huizer, Beacon Environmental

Attachments

Figure 1 – Location of Subject Lands  
Figure 2 – Base Map  
Figure 4 – Geologic Cross-Section A-A'  
Figure 5 – Wetland catchments  
Appendix A – Supporting Information  
Appendix B – Concept Plan



## 6.0 References

AquaResource Inc. and Niagara Peninsula Conservation Authority (NPCA), 2009. Water Availability Study for the Lake Erie North Shore Watershed Plan Area, Niagara Peninsula Source Protection Area.

Armstrong, D.K., 2017. Paleozoic geology of the Welland-Fort Erie area, southern Ontario; Ontario Geological Survey, Preliminary Map P.3811, scale 1:50 000.

Beacon Environmental, 2022. DRAFT Environmental Impact Study Addendum, Northland Estates, City of Port Colborne.

Burt, A., 2020. Results of the 2014-2017 drilling programs on the Niagara Peninsula: Graphic logs, descriptions and analytical data; Ontario Geological Survey, Miscellaneous Release – Data 383.

Chapman, L.J., and Putnam, D.F., 1984. The Physiography of Southern Ontario. Ontario Geological Survey, Special Volume 2, 270 p.

City of Port Colborne, 2021. Pre-Consultation Agreement, May 27, 2021, Westside Road Con. 2 PT Lot 31.

Conservation Ontario, 2013. Hydrogeological Assessment Submissions, Conservation Authority Guidelines for Development Applications.

Devlin, J.F., 2015. HydrogeoSieveXL: an Excel-based tool to estimate hydraulic conductivity from grain-size analysis.

Environment and Climate Change Canada, 2022. Climate Normals 1981-2010 Welland Station, ID 6136606.

Feenstra, B.H., 1984. Quaternary Geology of the Niagara-Welland Area, Map 2496. Ontario Geological Survey.

Groundwater Environmental Management Services (GEMS) Inc., 2020. Constraints Summary Report, Northlands Development. Prepared for 2600261 Ontario Inc.

Kingston, M.S. and Presant, E.W., 1989. The Soils of the Regional Municipality of Niagara, Report No.60 of the Ontario Institute of Pedology, Volume 1.

McCabe, G.J., and Markstrom, S.L., 2007. A monthly water-balance model driven by a graphical user interface. U.S. Geological Survey Open-File report 2007-1008, 6p.

Menzies, J., 2009. Diamicton. In: Encyclopedia of Paleoclimatology and Ancient Environments. Encyclopedia of Earth Science Series. Springer.

Ministry of Natural Resources and Forestry (MNRF), 2009. Onondaga Escarpment Wetland Complex, Wetland Evaluation.

Ministry of the Environment, Conservation and Parks, 2022. Water well records.

Ministry of the Environment, (Conservation and Parks), 2008. Design Guidelines for Sewage Works.

Ministry of the Environment, (Conservation and Parks), 2006. Assessment Report: Draft Guidance Module 3, Groundwater Vulnerability Analysis.

Ministry of the Environment, (Conservation and Parks), 2003. Stormwater Management Planning and Design Manual.

Mitsch, W.J., and Gosselink, J.G., 2007. *Wetlands*, 4<sup>th</sup> Edition.

Niagara Peninsula Conservation Authority (NPCA), 2021. EIS Review, (Northlands Subdivision). NPCA file No. PLOTH202100047. Letter for Landpro Planning Solutions from Jessica Abrahamse.

Niagara Peninsula Conservation Authority (NPCA), 2018. Digital Elevation Model.

Niagara Peninsula Conservation Authority (NPCA), 2017. Contemporary Watercourse Mapping.

Niagara Peninsula Conservation Authority (NPCA), 2010. Natural Areas Inventory, Ecological Land Classifications.

Ontario Geological Survey (OGS), 2003. Surficial geology of southern Ontario. Miscellaneous Release Data – 128. Project Summary and Technical Document, 53 pp.

Ontario Ministry of Agriculture, Food and Rural Affairs (OMAFRA), 2022. AgMaps  
<https://www.gisapplication.lrc.gov.on.ca/AIA/index.html?viewer=AIA.AIA&locale=en-US>

Sanderson, M., 2004. Weather and Climate in Southern Ontario. Department of Geography, University of Waterloo, Publication Series Number 58.

Shaheen & Peaker Limited, 2002. Geotechnical Investigation, West Side Road and Barrick Road, Port Colborne, Ontario. Prepare for 1526248 Ontario Limited c/o LGI Consulting Engineers.

Toronto and Region Conservation Authority, 2017. Wetland Water Balance Risk Evaluation.



Toronto and Region Conservation Authority, 2016. Wetland Water Balance Monitoring Protocol.


Toronto and Region Conservation Authority, 2012. Appendix D, Water Balance for Protection of Natural Features, Stormwater Management Criteria.

United States Department of Agriculture (USDA), 1986. Urban Hydrology for Small Watersheds.


Upper Canada Consultants, 2022. Northland Estates – Draft Plan of Subdivision.





<b>Location of Site</b>	
<b>Northland Estates Water Balance Study</b>	
 <b>Terra-Dynamics Consulting Inc.</b>	
<b>Prepared for: 2600261 Ontario Inc.</b>	<b>Figure 1</b>





- MECP Water Well Record
- Test Pit
- Soil Sample (March, 2022)
- Ground Surface Contour (mASL)
- Hydrogeologic Cross-Section A-A'
- Hydrography
- Subject Lands
- Wetlands**
  - SWD1 Oak Mineral Deciduous Swamp
  - SWT2 Mineral Thicket Swamp
  - Onondaga Escarpment
  - Locally Significant Wetland
- Surficial Geology**
  - Cherty limestone
  - Clay and silt

## Base Map


# Northland Estates Water Balance Study



Prepared for:  
**2600261 Ontario Inc.**

**Figure 2**

References: Niagara Peninsula Conservation Authority: Hydrography (1:2000), 2021; Wetlands. Ontario Geological Survey: Surficial Geology. Ministry of the Environment, Conservation and Parks: Water Well Information System Records, 2022.  
Map Date: 2022-05-03 D:\TerraDynamics\Projects\Alliance Northland Estates\ProjectFiles\Figure 2 - Base Map.qgz



SS Soil Sample, Hand-Auger

Well Water Level with year of measurement

EOH End of Hole

See Figure 2 for line of cross-section

### Hydrogeologic Cross-Section A-A'


### Northland Estates Water Balance Study



**Terra-Dynamics Consulting Inc.**

Prepared For:  
2600261 Ontario Inc.

Figure 4



Subject Lands

Ground Surface Contour (mASL)

Hydrography

General Direction of Drainage

#### Wetlands

SWD1 Oak Mineral Deciduous Swamp

SWT2 Mineral Thicket Swamp

30m Buffer of SWD1

#### Wetland Catchments

A

A'

B

B'

C'

D

Upgradient A

Upgradient B

## Wetland Catchments

### Northland Estates Water Balance Study



**Terra-Dynamics Consulting Inc.**

Prepared for:  
**2600261 Ontario Inc.**


**Figure 5**



## **Appendix A**

### **Supporting Information**

Figure A-1, OMAFRA Soils



**E3 Laboratories Inc.**

SS#4, 360 York Rd., Unit 10, Niagara-on-the-Lake, Ontario L0S 1J0

Email: info@e3labs.ca

Tel: (905) 641-9000, Fax: (905) 641-9001

**CERTIFICATE OF ANALYSIS**

Terra-Dynamics Consulting

Jayme Campbell

432 Niagara St

St. Catharines

L2M 4W3

Tel: Fax:

**Email: [jcampbell@terra-dynamics.com](mailto:jcampbell@terra-dynamics.com)**

Work Order No.: 2633081

Received : 2022-03-17

PO Number:

Reported: 2022-03-23

Project Name: Alliance Northland PC

Chain of Custody No.: 2633081

Client Sample ID	Sample		Parameter	Result	Unit	RDL	Date	Method
	Date	Lab ID					Analyzed	
<b>Sample 2</b>	2022-03-16	<b>712501</b>	T Time	See	Attached		2022-03-23	Subcontracted
<b>Sample 3</b>	2022-03-16	<b>712502</b>	T Time	See	Attached		2022-03-23	Subcontracted

Reported by:


Nilou Ghazi, Ph.D., P.Eng.  
Laboratory Manager

Page 1 of 1

All work has been performed using accepted testing methodologies, except where otherwise agreed to by the client in writing. Our total liability in connection with this work shall be limited to the amount paid by the client.  
Results relate only to items tested as received.



# PARTICLE SIZE DISTRIBUTION LS702/ASTM D422



Unified Classification System

SILT AND CLAY	SAND	GRAVEL
---------------	------	--------

----- sm envelope T = 8 - 20 min/cm  
----- ml envelope T = 20 - 50 min/cm

Estimated T = 50 min/cm

GRAVEL	1	%
SAND	19	%
SILT	47	%
CLAY	33	%

Project Name:	E3 Laboratories	Project No.:	111-53143-00 (2633081)
Location ID.:	Sample 2	Sample No./Depth:	712501

Sieve Size	% Passing Coarse	Sieve Size	% Passing Fine	Hydrometer (mm)	% Passing
37.5 mm	100.0	2.00 mm	94.18	0.035	63.0
26.5 mm	100.0	0.850 mm	89.4	0.017	55.0
19.0 mm	100.0	0.425 mm	86.2	0.008	43.6
13.2 mm	100.0	0.250 mm	84.0	0.003	35.5
9.50 mm	100.0	0.106 mm	80.8	0.001	28.7
4.75 mm	98.9	0.075 mm	79.2		


Note: More information is available upon request.

Tested by: WGH

Reviewed by:  Date: 22-Mar-22



# PARTICLE SIZE DISTRIBUTION LS702/ASTM D422



Unified Classification System

SILT AND CLAY	SAND	GRAVEL
---------------	------	--------

GRAVEL	1	%
SAND	13	%
SILT	47	%
CLAY	39	%

----- sm envelope T = 8 - 20 min/cm  
----- ml envelope T = 20 - 50 min/cm  
Estimated T = >50 min/cm

Project Name:	E3 Laboratories	Project No.:	111-53143-00 (2633081)
Location ID.:	Sample 3	Sample No./Depth:	712502

Sieve Size	% Passing Coarse	Sieve Size	% Passing Fine	Hydrometer (mm)	% Passing
37.5 mm	100.0	2.00 mm	97.69	0.042	70.1
26.5 mm	100.0	0.850 mm	96.4	0.020	60.7
19.0 mm	100.0	0.425 mm	94.8	0.008	51.2
13.2 mm	100.0	0.250 mm	93.1	0.003	41.7
9.50 mm	99.2	0.106 mm	88.1	0.001	36.0
4.75 mm	98.7	0.075 mm	85.4		

Note: More information is available upon request.

Tested by: WGH

Reviewed by:  Date: 21-Mar-22




K from Grain Size Analysis Report

Date: 20-Apr-22

Sample Name: Soil Sample 2 - Northland Estates

Mass Sample (g): 100 T (oC) 20

Poorly sorted clay with fines



Estimation of Hydraulic Conductivity	cm/s	m/s	m/d	de
Hazen	7.E-08	7.E-10	0.00	
Hazen K (cm/s) = d <sub>10</sub> (mm)	1.E-07	1.E-09	0.00	
Slichter	1.E-08	1.E-10	0.00	
Terzaghi	2.E-08	2.E-10	0.00	
Beyer	5.E-08	5.E-10	0.00	
Sauerbrei	4.E-08	4.E-10	0.00	
Kruger	5.E-05	5.E-07	0.04	
Kozeny-Carmen	4.E-06	4.E-08	0.00	
Zunker	3.E-06	3.E-08	0.00	
Zamarin	3.E-06	3.E-08	0.00	
USBR	3.E-08	3.E-10	0.00	
Barr	1.E-08	1.E-10	0.00	
Alyamani and Sen	9.E-06	9.E-08	0.01	
Chapuis	1.E-10	1.E-12	0.00	
Krumbein and Monk	3.E-05	3.E-07	0.03	
Shepherd	1.E-04	1.E-06	0.11	
geometric mean	9.E-07	9.E-09	0.00	
arithmetic mean	3.E-05	3.E-07	0.03	




K from Grain Size Analysis Report

Date: 20-Apr-22

Sample Name: Soil Sample 3 - Northland Estates

Mass Sample (g): 100 T (oC) 20

Poorly sorted clay with fines



Estimation of Hydraulic Conductivity	cm/s	m/s	m/d	de
Hazen	4.E-08	4.E-10	0.00	
Hazen K (cm/s) = $d_{10}$ (mm)	8.E-08	8.E-10	0.00	
Slichter	9.E-09	9.E-11	0.00	
Terzaghi	1.E-08	1.E-10	0.00	
Beyer	3.E-08	3.E-10	0.00	
Sauerbrei	3.E-08	3.E-10	0.00	
Kruger	6.E-05	6.E-07	0.05	
Kozeny-Carmen	3.E-06	3.E-08	0.00	
Zunker	2.E-06	2.E-08	0.00	
Zamarin	3.E-06	3.E-08	0.00	
USBR	2.E-08	2.E-10	0.00	
Barr	9.E-09	9.E-11	0.00	
Alyamani and Sen	3.E-06	3.E-08	0.00	
Chapuis	6.E-11	6.E-13	0.00	
Krumbein and Monk	8.E-05	8.E-07	0.07	
Shepherd	5.E-05	5.E-07	0.04	
geometric mean	4.E-07	4.E-09	0.00	
arithmetic mean	1.E-05	1.E-07	0.01	



66 No. 1820

ONTARIO WATER RESOURCES COMMISSION

The Ontario Water Resources Commission Act

## WATER WELL RECORD

UTM 10 Z 10 E5 R 10 NElev. 4 R 0602Basin 23 Welland

County or District

Con. 2Lot part 32Township, Village, Town or City Port ColborneDate completed 12

(day)

Dec66

month

year

Address RR 2 Port Colborne

## Casing and Screen Record

## Pumping Test

Inside diameter of casing 5 in.Total length of casing 6 ft.

Type of screen

Length of screen

Depth to top of screen

Diameter of finished hole 5 in.Static level 12 ft.Test-pumping rate 2 G.P.M.Pumping level 20Duration of test pumping 1 1/2 hrsWater clear or cloudy at end of test clearRecommended pumping rate 1 G.P.M.with pump setting of 25 feet below ground surface

## Well Log

## Water Record

## Overburden and Bedrock Record

From  
ft.To  
ft.Depth(s) at  
which water(s)  
foundKind of water  
(fresh, salty,  
sulphur)rubble  
shale0  
33  
2929 ft.fresh

For what purpose(s) is the water to be used?

Is well on upland, in valley, or on hillside?

Drilling or Boring Firm

Address

Licence Number

Name of Driller or Borer

Address

Date Dec 31 / 66


(Signature of Licensed Drilling or Boring Contractor)

Form 7 15M-60-4138

OWRC COPY

## Location of Well

In diagram below show distances of well from road and lot line. Indicate north by arrow.



CSS.S8





Instructions for Completing Form

- For use in the **Province of Ontario** only. This document is a permanent **legal** document. Please retain for future reference.
- All Sections **must** be completed in full to avoid delays in processing. Further instructions and explanations are available on the back of this form.
- Questions regarding completing this application can be directed to the Water Well Management Coordinator at 416-235-6203.
- All metre measurements shall be reported to 1/10<sup>th</sup> of a metre.**
- Please print clearly in blue or black ink only.

Well Owner's Information and Location of Well Information

F		MUN		CON		LOT	
C							

Address of Well Location (County/District/Municipality) <b>227 West Side</b>				Township				Lot		Concession	
RR#/Street Number/Name				City/Town/Village <b>Port Colborne</b>				Site/Compartment/Block/Tract etc.			
GPS Reading	NAD	Zone	Easting	Northing	Unit Make/Model	Mode of Operation:		<input type="checkbox"/> Undifferentiated <input checked="" type="checkbox"/> Averaged		<input type="checkbox"/> Differentiated, specify	
	<b>83</b>	<b>17</b>	<b>641476</b>	<b>4751823</b>	<b>Magellan</b>						

Log of Overburden and Bedrock Materials (see instructions)

General Colour	Most common material	Other Materials	General Description	Depth	
				From	To
black	Asphalt			0	.11
brown	Gravel			.11	.9
gray	limestone		hard.	.9	6

Hole Diameter		
Depth	Metres	Diameter
From	To	Centimetres
<b>6</b>	<b>6</b>	<b>10</b>

Water Record	
Water found at <b>4.5</b> Metres	Kind of Water
<input type="checkbox"/> m <input type="checkbox"/> Fresh <input type="checkbox"/> Sulphur <input type="checkbox"/> Gas <input type="checkbox"/> Salty <input type="checkbox"/> Minerals <input type="checkbox"/> Other:	<input type="checkbox"/> m <input type="checkbox"/> Fresh <input type="checkbox"/> Sulphur <input type="checkbox"/> Gas <input type="checkbox"/> Salty <input type="checkbox"/> Minerals <input type="checkbox"/> Other:
<input type="checkbox"/> m <input type="checkbox"/> Fresh <input type="checkbox"/> Sulphur <input type="checkbox"/> Gas <input type="checkbox"/> Salty <input type="checkbox"/> Minerals <input type="checkbox"/> Other:	<input type="checkbox"/> m <input type="checkbox"/> Fresh <input type="checkbox"/> Sulphur <input type="checkbox"/> Gas <input type="checkbox"/> Salty <input type="checkbox"/> Minerals <input type="checkbox"/> Other:
After test of well yield, water was	
<input type="checkbox"/> Clear and sediment free <input type="checkbox"/> Other, specify	
Chlorinated <input type="checkbox"/> Yes <input type="checkbox"/> No	

Construction Record				
Inside diam centimetres	Material	Wall thickness centimetres	Depth From	Metres To
<b>3.2</b>	<input type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input checked="" type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized	<b>.5</b>	<b>0</b>	<b>1.5</b>
	<input type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized			
	<input type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input checked="" type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized			
Screen				
Outside diam	<input type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input checked="" type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized	Slot No.	<b>1.5</b>	<b>6</b>
<b>4.2</b>		<b>10</b>		
No Casing or Screen				
<input type="checkbox"/> Open hole				

Test of Well Yield				
Pumping test method	Draw Down		Recovery	
	Time min	Water Level Metres	Time min	Water Level Metres
Pump intake set at - (metres)	Static Level			
Pumping rate - (litres/min)	<b>1</b>		<b>1</b>	
Duration of pumping _____ hrs + _____ min	<b>2</b>		<b>2</b>	
Final water level end of pumping _____ metres	<b>3</b>		<b>3</b>	
Recommended pump type <input type="checkbox"/> Shallow <input checked="" type="checkbox"/> Deep	<b>4</b>		<b>4</b>	
Recommended pump depth. _____ metres	<b>5</b>		<b>5</b>	
Recommended pump rate. (litres/min)	<b>10</b>		<b>10</b>	
If flowing give rate - (litres/min)	<b>15</b>		<b>15</b>	
	<b>20</b>		<b>20</b>	
	<b>25</b>		<b>25</b>	
If pumping discontinued, give reason.	<b>30</b>		<b>30</b>	
	<b>40</b>		<b>40</b>	
	<b>50</b>		<b>50</b>	
	<b>60</b>		<b>60</b>	


Plugging and Sealing Record		
Depth set at - Metres	Material and type (bentonite slurry, neat cement slurry) etc.	Volume Placed (cubic metres)
From To		
<b>0</b> <b>.3</b>	<b>concrete</b>	
<b>.3</b> <b>1.2</b>	<b>bentonite</b>	

Method of Construction			
<input type="checkbox"/> Cable Tool <input type="checkbox"/> Rotary (conventional) <input type="checkbox"/> Rotary (reverse)	<input checked="" type="checkbox"/> Rotary (air) <input type="checkbox"/> Air percussion <input type="checkbox"/> Boring	<input type="checkbox"/> Diamond <input type="checkbox"/> Jetting <input type="checkbox"/> Driving	<input type="checkbox"/> Digging <input type="checkbox"/> Other
Water Use			
<input type="checkbox"/> Domestic <input type="checkbox"/> Stock <input type="checkbox"/> Irrigation	<input type="checkbox"/> Industrial <input type="checkbox"/> Commercial <input type="checkbox"/> Municipal	<input type="checkbox"/> Public Supply <input type="checkbox"/> Not used <input type="checkbox"/> Cooling & air conditioning	<input checked="" type="checkbox"/> Other
Final Status of Well			
<input type="checkbox"/> Water Supply <input checked="" type="checkbox"/> Observation well <input type="checkbox"/> Test Hole	<input type="checkbox"/> Recharge well <input type="checkbox"/> Abandoned, insufficient supply <input type="checkbox"/> Abandoned, poor quality	<input type="checkbox"/> Unfinished <input type="checkbox"/> Dewatering <input type="checkbox"/> Replacement well	<input type="checkbox"/> Abandoned, (Other)

Well Contractor/Technician Information	
Name of Well Contractor <b>Geo Environmental Drilling</b>	Well Contractor's Licence No. <b>6607</b>
Business Address (street name, number, city etc.) <b>340 Market Dr Milton, ON</b>	
Name of Well Technician (last name, first name) <b>Hails Ryan</b>	Well Technician's Licence No. <b>T3212</b>
Signature of Technician/Contractor <b>X</b>	Date Submitted <b>2006 01 04</b>

Location of Well	
In diagram below show distances of well from road, lot line, and building. Indicate north by arrow. <b>See map.</b>	
Audit No. <b>Z 42216</b>	Date Well Completed <b>2006 01 04</b>
Was the well owner's information package delivered? <input type="checkbox"/> Yes <input type="checkbox"/> No	Date Delivered <b>2006 01 04</b>

Ministry Use Only	
Data Source	Contractor <b>6607</b>
Date Received <b>FEB 13 2006</b>	Date of Inspection <b>2006 01 04</b>
Remarks	Well Record Number



6607

Z42216

LEGEND:

- ⊕ Approximate Borehole Location
- BH 102

FEB 13 2006



Trow Associates Inc.

428 Millen Road, Stoney Creek, Ontario L8E 3N9  
Telephone: (905) 664-3300  
Fax: (905) 662-4144

SCALE: N.T.S

DATE: January, 2004

Project No.: HAEN-00069891B/E

DRWN.: MW

CHKD.: KG

BOREHOLE LOCATION PLAN  
Phase II Environmental Site Assessment  
287 West Side Road  
Port Colborne  
ONTARIO

DRAWING

2

Follow the **COVID-19 restrictions and public health measures** (<https://covid-19.ontario.ca/public-health-measures>) and **book your appointment to get vaccinated** (<https://covid-19.ontario.ca/book-vaccine/>).

# Map: Well records

This map allows you to search and view well record information from reported wells in Ontario.

Full dataset is available in the [Open Data catalogue](https://data.ontario.ca/dataset/well-records) (<https://data.ontario.ca/dataset/well-records>).



[Go Back to Map\(\)](#)

## Well ID

Well ID Number: 7117365  
Well Audit Number: M03054  
Well Tag Number: A074891  
*This table contains information from the original well record and any subsequent updates.*

This well is part of a well cluster.  
The information below is extracted from the cluster well record.  
More information on the cluster well record (related to other wells in the cluster) [is also available.](#)

## Well Location

Address of Well Location	287 WEST SIDE RD
Township	PORT COLBORNE CITY
Lot	
Concession	

<b>County/District/Municipality</b>	NIAGARA (WELLAND)
<b>City/Town/Village</b>	Port Colborne
<b>Province</b>	ON
<b>Postal Code</b>	n/a
<b>UTM Coordinates</b>	NAD83 — Zone 17 Easting: 641455.00 Northing: 4751710.00
<b>Municipal Plan and Sublot Number</b>	
<b>Other</b>	

## Overburden and Bedrock Materials Interval

General Colour	Most Common Material	Other Materials	General Description	Depth From	Depth To
BRWN	SAND	GRVL	CGRD	0 m	.9 m
GREY	LMSN		FCRD	.9 m	5.3 m

## Annular Space/Abandonment Sealing Record

Depth From	Depth To	Type of Sealant Used (Material and Type)	Volume Placed
0 m	3.5 m	BENTONITE CHIPS	

## Method of Construction & Well Use

Method of Construction	Well Use
Rotary (Air)	Monitoring
AUGER	

## Status of Well

Test Hole

# Construction Record - Casing

Inside Diameter	Open Hole or material	Depth From	Depth To
3.2 cm	PLASTIC	0 m	3.8 m

# Construction Record - Screen

Outside Diameter	Material	Depth From	Depth To
4.2 cm	PLASTIC		

# Well Contractor and Well Technician Information

Well Contractor's Licence Number: 6607

# Results of Well Yield Testing

After test of well yield, water was

If pumping discontinued, give reason

Pump intake set at

Pumping Rate

Duration of Pumping

Final water level

If flowing give rate

Recommended pump depth

Recommended pump rate

Well Production

Disinfected?N

# Draw Down & Recovery

Draw Down Time(min)	Draw Down Water level	Recovery Time(min)	Recovery Water level
SWL	3 m		
1		1	
2		2	
3		3	
4		4	
5		5	
10		10	
15		15	
20		20	
25		25	
30		30	
40		40	
45		45	
50		50	
60		60	

## Water Details

Water Found at Depth	Kind
3.9 m	Fresh

## Hole Diameter

Depth From	Depth To	Diameter
0 m	1.2 m	21 cm

1.5 m    5.3 m    10 cm

---

**Audit Number:** M03054

**Date Well Completed:** August 19, 2008

**Date Well Record Received by MOE:** January 08, 2009

Updated: October 18, 2021

Published: March 20, 2014

## Related

[How to use a Ministry of the Environment map \(/page/how-use-ministry-environment-map#wells\)](/page/how-use-ministry-environment-map#wells)

Technical documentation: Metadata record (<https://data.ontario.ca/dataset/well-records/resource/3031344e-e3f2-48d5-888c-c1deadfd2f77>)

---

[about Ontario \(https://www.ontario.ca/page/about-ontario\)](https://www.ontario.ca/page/about-ontario)

[accessibility \(https://www.ontario.ca/page/accessibility\)](https://www.ontario.ca/page/accessibility)

[news \(http://news.ontario.ca/newsroom/en\)](http://news.ontario.ca/newsroom/en)

[privacy \(https://www.ontario.ca/page/privacy-statement\)](https://www.ontario.ca/page/privacy-statement)

[terms of use \(https://www.ontario.ca/page/terms-use\)](https://www.ontario.ca/page/terms-use)

[© Queen's Printer for Ontario, 2012–22 \(https://www.ontario.ca/page/copyright-information-c-queens-printer-ontario\)](https://www.ontario.ca/page/copyright-information-c-queens-printer-ontario)






**Appendix B**

**Northland Estates Draft Plan of**

**Subdivision**

# NORTHLAND ESTATES

## CITY OF PORT COLBORNE



### KEY PLAN

N.T.S.

### DRAFT PLAN OF SUBDIVISION

### LEGAL DESCRIPTION

PART OF LOT 31, CONCESSION 2  
GEOGRAPHIC TOWNSHIP OF HUMBERSTONE  
CITY OF PORT COLBORNE  
REGIONAL MUNICIPALITY OF NIAGARA

### OWNER'S CERTIFICATE

BEING THE REGISTERED OWNER, I HEREBY  
AUTHORIZE UPPER CANADA CONSULTANTS TO  
PREPARE AND SUBMIT THIS DRAFT PLAN OF  
SUBDIVISION TO THE CITY OF PORT COLBORNE  
FOR APPROVAL.

2600261 ONTARIO INC.

DATE

### SURVEYOR'S CERTIFICATE

I HEREBY CERTIFY THAT THE BOUNDARIES OF  
THE LANDS TO BE SUBDIVIDED ARE  
CORRECTLY SHOWN.

ROY S. KIRKUP, B.Sc., O.L.I.P., Ontario Land Surveyor DATE  
KIRKUP MASCOE URE SURVEYING  
(a Division of J.D. Barnes Limited)

### REQUIREMENTS OF SECTION 51(17) OF THE PLANNING ACT

- a) SEE PLAN  
b) SEE PLAN  
c) SEE PLAN  
d) SEE PLAN  
e) SEE PLAN  
f) SEE PLAN  
g) SEE PLAN  
h) MUNICIPAL WATER  
i) VARIOUS TEXTURES  
OVER BEDROCK  
j) SEE PLAN  
k) FULL SERVICE  
l) SEE PLAN

### LAND USE SCHEDULE

LAND USE	LOT/BLOCK	# OF UNITS	AREA(ha)	AREA(%)
SINGLE FAMILY RESIDENTIAL	LOT 1-125	125	5.176	30.89
STREET TOWNS RESIDENTIAL	BLOCK 126-135	50	1.024	6.11
MIXED USE RESIDENTIAL/COMMERCIAL	BLOCK 136	50	0.686	4.09
ENVIRONMENTAL PROTECTION AREA	BLOCK 137		5.700	34.01
PARK	BLOCK 138		0.509	3.04
STORMWATER MGMT AREA	BLOCK 139		0.962	5.74
0.3m RESERVE	BLOCK 140-141		0.001	0.01
ROADWAY			2.700	16.11
TOTAL		225	16.758	100.00

DEVELOPABLE AREA = 11.06 ha.  
DEVELOPABLE DENSITY = 20.34 units/ha

ISSUED FOR	YYYY-MM-DD
REVISION	DATE



### DRAFT PLAN OF SUBDIVISION

DRAFTING MK

DATE MAY 13, 2022

PRINTED MAY 26, 2022

SCALE 1:1500

DWG No.

21132-DP

REV

0

### GREENFIELD DENSITY CALCULATION

	People		Jobs		
	Units	Ratio	Units	Ratio	Total
	225 Dwellings	2.28 people per dwelling <sup>1</sup>	225 Dwellings	5% "at home" employment	11.25 Jobs
			16,576.42ft <sup>2</sup> of commercial space	1 employee per 500ft <sup>2</sup> of commercial space <sup>2</sup>	33.15 Jobs
Subtotal	513 people		44.40 jobs		
Total	557.40 people and jobs				
Land Area	11.058 hectares (exclusive of the Environmental Protection Area)				
Greenfield Density	50.41 people and jobs per hectare				